

ISUZU 6m³ Sewage Suction Vacuum Tank Truck[Ⓢ]

General [Ⓢ]	Vehicle Brand [Ⓢ]	VELDLION [Ⓢ]
	Chassis Brand [Ⓢ]	ISUZU [Ⓢ]
	Overall Dimension [Ⓢ]	6700*2300*2700mm [Ⓢ]
	GWW <u>Kerb Weight</u> [Ⓢ]	10,000kg/15,480kg [Ⓢ]
Cab [Ⓢ]	Cab Capacity [Ⓢ]	3 persons allowed [Ⓢ]
	Air Conditioner [Ⓢ]	Air conditioner equipped [Ⓢ]
Engine [Ⓢ]	<u>FuelType</u> [Ⓢ]	Diesel [Ⓢ]
	Engine Brand [Ⓢ]	ISUZU, 4HK1-TCG40[Ⓢ]
	Power [Ⓢ]	190HP (139KW)[Ⓢ]
	Displacement [Ⓢ]	5193 ml [Ⓢ]
	Emission Standard [Ⓢ]	<u>Euroll</u> , Euro IV [Ⓢ]
Chassis [Ⓢ]	<u>DriveType</u> [Ⓢ]	4X2, <u>left hand drive</u>[Ⓢ]
	Transmission [Ⓢ]	ISUZU MLD, Manual, 5-Forward & 1-Reverse[Ⓢ]
	Wheelbase/ <u>No.of axle</u> [Ⓢ]	3815mm / 2 [Ⓢ]
	<u>Tyre Specification</u> [Ⓢ]	8.25-16[Ⓢ]
	<u>Tyre Number</u> [Ⓢ]	6 <u>tyres and 1 spare tyre</u>[Ⓢ]
	Max Speed [Ⓢ]	100km/h [Ⓢ]
	Paint [Ⓢ]	<u>Metalic paint</u> [Ⓢ]
Super structure [Ⓢ]	Vacuum Tank Capacity [Ⓢ]	6m³[Ⓢ]
	Tank Material [Ⓢ]	Carbon Steel [Ⓢ]
	Suction Head [Ⓢ]	7m [Ⓢ]
	Vacuum Pump [Ⓢ]	High <u>efficiency, vacuum</u> rate up to 93%, quick suction + and discharge [Ⓢ]
	Suction Hose [Ⓢ]	High <u>quality, wire strengthened</u> hose [Ⓢ]

Install vacuum Pump drive by engine through PTO,hydraulic system,multi-way valve,pressure gauges,water-gas separator,oil-gas separator,oil tank, reservoir,level inspection window and suction hose.

Rear door can be hydraulic opened for complete discharge of solid stuff.

↓

All other standard accessories: Tool kit,English manual .

Optional

- 1.Tank material could be mild steel stainless steel
- 2.Italy vacuum pump is available.

□□□□□□ □□□□:







