

□□ □□□□□ □□□□□□ □□□□□ □ □□□□□ □□□□□□□ □□□□□□ □□□□□ □□□ □□□□□□ □□□□□□ □□□□□□ □□□□ □ □□□□□□□.

(1).Apacity Truck Apacity: 3-30CBM □ 30-3 □□□□□ □□□□ □□□□□M3

(2).□□□□□□□ □□□□□□□ □□□□ □ □□□□□□ □□□□□ □□□□ □□ □□ :□□□□□□□ □□□□ □□□□□□□□

□□□□□□ □□□□□ □ □□□□ 4 □ □□□□ 3 □ 2 □□□□ □ 1 □□□□ □□□□ :□□□□□□□□□□ □□□□□.(3) □□□□ 5

□□□□ :□□□□□□□ □□□□.(4) Isuzu □ Howo □ Jac □ Dongfeng □ Foton □□□

□□□□□ □□□□□ □ □□□ □□□□ □ □□□□□ □□□□□ □□□□□ □□□□ □□□□ □□□□ □□□□ □ □□□□□□ □□□□□ □□□□□ □ □□□□□ □□□□ □ □□□□ □□□□ □ □□□□ □□□□ □ □□□□□ □□□ □ □□□□□□□□ □□□□□ □□□□□.

Complete Vehicle Parameter	
Vehicle	HOWO fuel tanker truck
Overall dimensions (mm)	7990 x 2500 x 2900
Fuel tanker	10000
GVW (kg)	Appro × 14845
Curb weight (kg)	Appro × 6650
Loading weight (kg)	Appro × 8000
Wheel base (mm)	4200
Max speed (Km/h)	80
HOWO Truck Chassis Parameter	
Cabin	One and half cabin, a sleeper, power steering, air conditioner,3 passengers
Traction system	4×2
Engine	Brand : CUMMINS Model : ISF3.8s3168 Engine power : 168hp Type : diesel, 4 cylinder, turbocharged. Displacement : 3760ml Emission standard : Euro 3
Transmission	6 forward,1 reverse , manual operated
Tire model	8.25R20
No.of tires	6+1pcs
Fuel Tanker Parameter	

Characteristic	1) 10000 liter fuel tanker. 2) Fuel tanker material is carbon steel. 3) Fuel tank thickness 4.75mm,tank head thickness 5.1mm. 4) One compartment fuel tank. 5) One set refuel equipment. 6) Equipped with oil pump, PTO. 7) Equipped with European standard manhole. 8) Equipped with aluminum alloy emergency cut off valve. 9) Connection method: the left and right sides and the lower part of the protection are welded. 10) Tool box.
----------------	--

1. 主要性能指标:





Whatsapp & Telephone: +86-18607222773 Email: brenda@clewtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-1860722773 Email: brenda@clclwtruck.com