		5.4pt 0cm 5.4pt;□□□15.85pt">"			
O O;OOOOOOO1.		5.4pt 0cm 5.4pt;			
Q235B_0 0 0;00000001. 0000 000000	0pt; 1.0pt; 0cm	5.4pt 0cm 5.4pt;□□□4.5pt">"			
" [][][kg[]	39800	□□ □□12980×2500×3820 ፴፴			
kg_	" 28000	" - /1860 □/ □□ □□			
kg_	" 11800	□□ " " □□ 7200+1310+1310			
M3_	44	 			
ппп	n	,,			
	3				
" 00 00	n				
Ш Ш "	Fuhua13t[]Fuhua15t[]16T				
	<pre>□BPW12T□14T □□□□□</pre> 28T				
	90[]				
ii ₀₀₀	00000000000000000000000000000000000000	_			
" III	" 	1			
]			
IIII.Application	00000000 00000' 000 1 5 0000				

. 45000



PRODUCT DETAILS



01

Oil Tanker Semi Trailer is a tanker with a trailing head connected to the trailing section. Compared with the conventional single tanker tanker tanker tanker, oil transport can effectively improve the transportation efficiency. In the same tonnage situation, reduce transportation costs, saving fuel consumption.

02

The tank body is made of 4mm or 6mm high-quality carbon steel according ,The shape of the tank body is divided into oval or square round tanks, which can contain 1-4 kinds of oil products. Can also produce heating and heat preservation series tanks.





03

A plurality of anti-wave baffles are arranged in the tank body. High pressure gas leak test is adopted to ensure that the tank body has high strength, stable center of gravity and safe and stable vehicle transportation.

PRODUCT ADVANTAGES

- Heavy duty and extra durability designed; Opting for high tensile steel Q345B, welded by automatic Submerged-Arc processes.
- 2. Heavy machinery suspension with leaf spring.
- 3.Two-line brake system with automatic brake system/chamber.
- 4.Welding tightness is strictly tested for solid tires, which are highly elastic and wear-resistant.
- 5.The material of the storage tank can be aluminum alloy, carbon steel, stainless steel, etc.

