

<b>Main specifications</b>			
Product model、 name	CLQ5310GY5D fuel tanker truck		
Gross weight(Kg)	31000	Driving type	8x4
Payload (Kg)	18735	Overall dimension (mm)	11990×2500×3300,3690
Curb weight(Kg)	12135	Cab seats (man)	3
Approach/departure angle (°)	26/10	Front/rear hang(mm)	1460/3030
Axle No.	4	Wheelbase (mm)	1950+4250+1300
Axle load(Kg)	6500/6500/18000	Max speed(Km/h)	80
<b>Chassis specifications</b>			
Chassis model	DFL1311A4	Manufacture	Dongfeng Motor Co.,Ltd
Brand name	DongFeng	Overall dimension (mm)	11475×2500×3030,3600,3690
Tire specification	295/80R22.5	Tires No.	12+1
Steel spring number	8/8/10	Front track(mm)	1940/1940
Fuel type	diesel	Rear track(mm)	1860/1860
Emission standard	Euro 3	Gear box	12 forward gears and 2 reverse gears
Cab	D310 Flat top and double cab, gasbag shock the driver seat, single dashboard, with air conditioning		
Engine model	Engine manufacture	Displacement(ml)	Power(Kw)
L340 33	Dongfeng Cummins Engine Co., LTD	9460	250
<b>Performance</b>			
Tank capacity ( Liter)	32000		
Tank material	Q235 carbon steel.		
Transport medium	Petrol or diesel.		
<b>Main Characteristic</b>			
<p><b>A</b>, with multiple baffle plates in the tank, the tank has the advantages of high intensity, stability, transporting safety etc.</p> <p><b>B</b>, Oil pump is installed to suck or discharge oil, with high suction pressure and speed.</p> <p><b>C</b>, according to users' needs, the tank can be designed as a single compartment or several compartments to contain different oils.</p> <p><b>D</b>, according to users' needs, the side or the rear of the tank can be installed 1 to 3 self-flowing valves.</p>			

□□□□





