

## Shacman 8×4 50-60T 360°

<b>Cabin</b>	Driving type 8x4, right hand driven	
	Two seats, with A/C and one sleeper, 70°hydraulically tillable to the front.	
<b>Vehicle Main Dimensions</b>	Overall dimensions (L x W x H)mm	12000×2500×3600
	Wheel base (mm)	1800+4600+1350
	Wheel track (front/rear) (mm)	2022/1830
<b>Weight in KGS</b>	Tare Weight(KGS)	24000
	Front axles loading capacity(KGS)	2x7500
	Rear axles loading capacity(KGS)	2x16000
<b>Max. driving speed(km/h)</b>	75	
<b>Engine</b>	Brand	CUMMINS
	Model	ISME385-30
	Type	4-stroke direct injection,6-cylinder in-line with water cooling, turbo-charging and inter-cooling
	Horse Power(HP)	385HP
	Emission standard	Euro 2
<b>Gearbox</b>	12JSD180T, 12 speed forward and 2 reverse gear	
<b>Clutch</b>	Reinforced diaphragm clutch, diameter 430mm	
<b>Steering</b>	Integral circulation ball power steering	
<b>Oil tank</b>	400 liters	
<b>Tire</b>	12.00R20 tires, 12 pieces with one spare	
<b>Special Device For Wrecker System</b>		
<b>Hoisting Organ</b>	Rated under-pulling capacity	60000
	Max Under-hoisting Capacity (kg)	30000

	Max Under-hoist length (mm)	3000
	Under hoisting work angle	-10~85°
<b>Lifting Organ</b>	Max lifting capacity(kg)	60000
	Max lifting high(mm)	11680
	Telescope length(mm)	6000
	Winch	30000kgs×2
	Steel rope	50M,Φ30
	Crane luffing angle	5°~ 60°
	Crane rotation angle	360°All Rotation
<b>Landing Leg</b>	Distance between front legs(mm)	7000
	Distance between rear legs(mm)	4000





Whatsapp & Telephone: +86-18607222773 Email: [brenda@clclwtruck.com](mailto:brenda@clclwtruck.com)





Whatsapp & Telephone: +86-18607222773 Email: [brenda@clciwtruck.com](mailto:brenda@clciwtruck.com)