

Truck brand	Japanese brand	Cabin	with A/C
Dimensions(mm)	8200*2500*3200 mm	Wheelbase(mm)	4500
Curb weight(kg)	9450 kgs	Front/Rear Axle loading(kg)	6300/13000 kg
Wheel track (front/rear) (mm)	1960/1855 mm	Front/Rear overhang(mm)	1335/1880 mm
Tire	10.00R20, total 7 pieces	Engine	266hp, Euro2
Sewage Suction & Cleaning System			
Sewage tank capacity	10000 liters	Tank material	Q235 carbon steel
Vacuum pump pressure	400 Pa	Inlet and Outlet pipe	108mm dia
Main parts	1. Water-gas separator 2. Oil-gas separator 3. Four way valve 4. Safety valve 5. Anti overflow valve 6. Anti overflow warning device 7. Hydraulic control rear cover 8. Tipping sewage tank body		

Features

A [vacuum truck](#) is a tank truck with a heavy duty vacuum designed to pneumatically load solids, liquids, sludge or slurry through suction lines typically 2-4" in diameter with 3" being the norm. The typical pump used in the industry is the rotary vane vacuum pump. The truck can be configured to be a direct PTO/belt or a PTO/hydraulic drive system. There are two different ways to mount the pump either directly on the truck with PTO drive or on the trailer with a pony motor. Each application has different handling characteristics.

Reference picture□



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com