## L'équipement du camion BOBTAIL LPG:

- 1. Compteur de pression
- 2. Compteur de température
- 3. Vanne de coupure d'urgence
- 4. Vanne sûre
- 5. Sécurité et prise de gaz
- 6. Pompe GPL

General	Overall Dimension	7000×2300×2600mm			
	Total Mass	7045Kg			
	Rated Payload	2500Kg			
	Kerb Weight	4395Kg			
Cabin	Cab Capacity	2 persons allowed			
	Air Conditioner	With air conditioner			
Engine	Model/Rated Power	YC4E140-33 / 140HP			
	Type	4-cylinder inline			
	Displacement	4256ml			
	Emission Standard	Euro 3			
	manufacturer	China Engine			
Chassis	Drive Type	4X2, Left Hand drive			
	Transmission	5forwards 1reverser			
	Wheelbase/No. of axle	3800 mm / 2			
	Tyre Specification	7.50R16			
	Tyre Number	6 tyres and 1 spare tyre			
	Max Speed	95 km/h			
	Paint	Metallic paint			
performance parameter	Capacity of tank	5000Liters			
	Inner diameter	1500mm			
	Lenght of tank body	3070mm			
	Tank body net weight	2832kgs			
	Design pressure	1.77Mpa			
	Design temperature	50℃			
	Thickness of tank body	10mm			
structural	Elliptical head, round tank	CONTRACT A SECURIOR CONTRACT AND THE SECURIOR SE			
style	The second secon				
Inspection test	proof pressure	2.30Mpa			
	Air tightness test pressure	1.77Mpa			
	Pressure after gas replacement	0.05-0.1Mpa			
	Non-destructive testing ratio	100%			
	Oxygen content in tank	<3%			
	name	model	specs	QΤ	
	Floating Ball Level Meter	UQZ-25P	1500	1	
	Pressure meter	Y-100T	0-4Mpa	1	
Safety	Temperature meter	WTQ-280	-40℃-60℃	1	
accessories	Safe valve	A412F-25-14	DN50/DN25	1/1	
	Emergencey cutoff valve	QGJ43F-25-7-8	DN50/DN25	2/2	
	Shut off valve	J24Q-64	DN6	2	
	Ball valve	Q41F-25P-8B/9B	DN50/DN25	1/1	
Other	LPG Pump				
attached	25m length hose reel.				
components:					
Painting	One anti corrosion and zinc-rich prim	er and final painting	will be accor	dance v	
1554	customer need.		78		

Images de référence:



















