

General Technical Parameters			
Overall Dimension		5995×2060×2950 (mm)	
Gross Vehicle Weight		4495(Kg)	
Curb Weight		3255(Kg)	
Chassis Specification			
Chassis Brand		ISUZU	
Drive model		4*2	
Cabin		Double, Left Hand Driving, with air conditional	
Number of Passengers		2-3	
Engine	Model	4-stroke direct injection , 6-cylinder in-line with water cooling, inter-cooling, EGR	
	Power	85KW/116HP	
	Emission standard	EURO 6	
	Displacement	2771(ml)	
	Fuel type	Diesel	
Gearbox		5Forwards & 1Reverse	
Brake System		Air break	
Wheel Base		3360mm	
Front/Rear Axle Loading		1500/3000(Kg)	
Approach/Departure Angle		23/12(°)	
Overhang		1250/3545(mm)	
Tire		7.00R16	
Max Driving Speed		90(km/h)	
Upperstructure Specification			
Cargo Body	Dimension	2770×1850×380(mm)	
	Material	Q235 carbon steel	
	Cargo Thickness	Side 1.5mm, Bottom 2.5mm	
Working System	Boom Type	Straight 3-Arm telescopic boom	
	Crane	Crane Brand	XCMG or SANY or CLW
		Range of Sprayer	30m
		Max Lifting Moment	25(T.M)
		Max Lifting Capacity	2000(kg)

		Max lifting height	12(m)
		Rotation angle	360(°)
		Installation space	1150(mm)
		Recommended power	30(kw)
		Maximum working pressure	26(Mpa)
		Max Flow	63(l/min)
		Crane weight	3800(kg)
		Oil tank capacity	160(L)
	Leg	Leg type	H type
		Leg Span	2.28-5.9(m)
	Hydraulic system	Pressure	18(M pa)
		Capacity	70(l)
Other Configuration	Control system in 2 side; diamond palt, yellow warning fire; 2.5T arm, etc.		
Options	Caution light, air condition, inlet valve, medicine tray, pneumatic valve, cylinder, etc.		

Images de référence:







Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com