□□□□□□□□□□ □□□□□□□□□□□□ □□□□□ □□□□□ □□ □□□□:
□□□□□□□□□□□/□□□□□□□ □□□□ □□□□□ □□ □□□□□□
1. □□ □□□□□ □□□□ □□ □□□□ □□□□□□□ □□ □□□□ □□□□□□□ □□ □□□□□ □□□□ □□ □□□□ □□ □□ □□□□□□□ (□□□□□□ □□□□□□□□ □□□□□□□□□□□□ □□□□□□) □□ □□□□□ □□
□□ □□□□ □□□□ □□□□□ □□□□□
2. □□□□ □□□□ □□□□□□: □□□□□ □□□□□ □□ 40% □□□□□□□
3. □□□□-□□□□□□□□□, □□□□-□□□□□□□□, □□□□□-□□□□□□□, □□□□□ □□ □□□□□ □□□□□□□□□□□□
4. □□□□□ □□□□□ □□ □□□□ □□□□□□□□□ □□□□□ □□□□ □□□□□ □□□□□□□□ □□ □□□□□□□ □□□□ □□□□□□ □□□□ □□□□ □□□□□□ □□□□□□□□□□ □□□□ 50-80 □□□□ □□
□□□□□, □□ □□□□□ □□□□□□ □□□□□□ □□□□□□□□□□ □□□□□□□□□ □□□□□□□ □□□□□ □□□□
5. □□□□□□□ □□□□□ □□□□□ □□ □□□□□□: 10-40 □□□□; □□□□□□□ □□□□□ □□ □□□□□□□: 5-70CBM. □□□□□□□ □□□□□ □□ □□□□□□□□ □□□□□□□□□ □□
□□□□□ □□□□ □□□□□□□ □□ □□□□□□ □□ □□□□□□□ □□□□□ □□, □□□□□ □□□□□□□ □□□□ □□□□ □□□□□□□□ □□ □□□□, □□□□□□ □□□□ □□□□□:
□□□□□ □□□□-□□□□ □□ □□□□□-□□□□□
6. □□□□□□□□ □□□□□ □□□□□□□ □□□□□□□□□: □□□□□□□□ □□□□□□□, □□□□□□ □□□□□□ □□□□□□□ □□□□□□□ □□□□□□. □□□□ □□□□□□□□, □□□□□□□□□□, □□□□□ □□□□□□□ □□□□□ 0° C ~ -20° C □□ □□□□□ □□□□ □□ □□□□ □□□□□□□□ □□□□□□□□ □□ □□□□ □□□□□ □□□□ □□□□□□ □□□□□□ □□□□□ □□
□□□□□□□, □□□□□□□□□□ □□□□□□□, □□□□□□□□□□ □□□□□□, □□ □□□□□□ □□□□, □□□□□ □□□□□□□□□□□□□□□□ □□□□□□□, □□ □□□□, □□□□□ □□□□□□□□ □□ □□□□□□□ □□ □□□□□□ □□□□□□□□□□□□□□□ □□□□□ □□ □□□□□ □□□□□□□

General Technical Parameters				
Overall Dimension	7025*2590*3300(mm)		Gross Vehicle Weight	8280(Kg)
Curb Weight	4085(Kg)		Loading Weight	4000(Kg)
Chassis Specification				
Chassis parameters	Chassis Brand		ISUZU	
	Cabin		Single, Left Hand Driving, with A/C	
	Engine	Model	4KH1CN6HB, 4 Cylinders	
		Power	130HP	
		Emission standard	EURO VI	
		Displacement	2.999L	
		Fuel type	Diesel	
	Gearbox		MSB, 5 Forward & 1 Reverse Gear	
	Front and Rear Axle load		3.3T/5.5T	
	Wheel base		3815(mm)	
	Overhang(Front/Rear)		1130/1505(mm)	
	Angle(Approach/departure)		20/16(°)	
	Brake System		Oil brake	
	Steering Gear		Power Assistant	
	Tire		7.00R16 8PR, 6 Pieces with 1 Spare Tire	
	Maximum speed		105(km/h)	
Superstructure				
Van	Box size		5020*2100*2100(mm)	
	Material		Fiberglass	
	Insulating Layer		8cm Polyurethane Foam	
Truck refrigeration unit	Brand		THERMOKING/CARRIER/other chinese brand	
	Applicable temperature (°C)		-18~0	
Remarks	Part Optional: Ventilation slot Hook External power supply			

□□□□□□ □□□□□:

ISUZU
Whatsapp & Telephone: +86-18607222773
Email:brenda@cicwtruck.com

ISUZU
Whatsapp & Telephone: +86-18607222773
Email:brenda@clclwtruck.com

ISUZU
Whatsapp & Telephone: +86-18607222773
Email:brenda@clclwtruck.com

冷藏车F类
Whatsapp & Telephone: +86 18607222773
Email:brenda@clclwtruck.com

ISUZU
Whatsapp & Telephone: +86-18607222773
Email:brenda@clclwtruck.com

冷藏车厢
Whatsapp & Telephone: +86-18607222773
Email:brenda@ciclwtruck.com

Whatsapp & Telephone: +86-18607222773
Email:brenda@clclwtruck.com

冷藏车F类
Whatsapp & Telephone: +86-18607222773
Email:brenda@clclwtruck.com

冷藏车F类
WhatsApp & Telephone: +86-18607222773
Email:brenda@clclwtruck.com