

ISUZU Fire Truck

Name	ISUZU Fire Truck		Chassis Model	QL10703HWRY	
Vehicle parameters	GVW(kg)	6545	Overall Dimension (mm)	6350×1980×2750	
	Rated load (kg)	2000	Steering Wheel	LHD	
	Curb weight (kg)	4170	Wheelbase (mm)	3360	
	Driving Type	4*2			
Engine parameters	Model	4JB1CN	Emission Standard	Diesel, Euro 4	
	Horse Power (hp)	98	Displacement (ml)	2771	
	4 stroke, 4-cylinders in line, water cooling				
Gear box	5 forward and 1 reverse				
Performance Parameter	Max Speed (km/h)	95	Wheel Tread(mm)	Front Axle	1504
	Cab Seat	2+3		Rear Axle	1425
	Leaf Spring	8/6+5	Suspension (mm)	Front Suspension	1015
	Tire No.	6+1		Rear Suspension	1880
	Tire Specification	7.00R15	Driving Angle(° )	Approach Angle	24
	Axle No.	2		Departure Angle	14
	Special Function	Capacity	Water tank 2500L		
Fire Pump		1. CB10/20, 20L/S, pressure:1.0MPa 2. Suction time ≤ 35s (7m suction depth ) centrifugal pump			
Fire Monitor		1. PS20, 20L/S, pressure: 1.0Mpa 2. Fire nozzle range: water ≥45m			
Performance Description	Double row cab with 4 doors; Hidden tank, material is carbon steel Q235A, with thickness 4 mm; Truck body with aluminum alloy rolling door; PTO control indicator installed in cab, also with 100W siren, LED alarm lamp, sign light, lighting switch, rear lighting and etc.				

ISUZU Fire Truck



Whatsapp & Telephone: +86-18607222773 Email: [brenda@clclwtruck.com](mailto:brenda@clclwtruck.com)



Whatsapp & Telephone: +86-18607222773 Email:brenda@clclvtruck.com





Whatsapp & Telephone: +86-18607222773 Email: [brenda@ciclwtruck.com](mailto:brenda@ciclwtruck.com)





Whatsapp & Telephone: +86-18607222773 Email: [brenda@clcwtruck.com](mailto:brenda@clcwtruck.com)



Whatsapp & Telephone: +86-18607222773 Email: [brenda@clclwtruck.com](mailto:brenda@clclwtruck.com)

### 01 EQUIPMENT CONFIGURATION

Free 6 technical documents, at least 34 fire extinguishing equipment and 7 demolition rescue tools



### 02 FIRE FIGHTING PUMP

With independent fire pump room, operation is convenient for fire fighters. according to capacity, we have CB10/20, CB10/30, CB10/40, CB10/60

### 03 FIRE FIGHTING GUN

Reliable performance, high pump flow rate high, far throw range. According to capacity, we have PS20, PS30, PS40, PS50



### 04 CONTROL INTEGRATION

With intelligent control integration system, ensure the stability of the entire operating vehicle. The whole truck body anti preservative treatment, welding is firm, smooth and even.

