```
496.5000pt; 000000-00000: 6.7500PT; 0000000-0000: 6.7500pt; 0000: 000 0000: 000000-
MSO-BORDER-BOTTOM-ALT: [][] [][][; MSO-BORDER-INSIDEH: 0.7500PT [][][][] WindowText;
MSO-BORDER-INSIDEV: 0.7500PT ATSET WINDOWTEXT; MSO-PADDING-ALT: 0.0000PT 0.0000PT
0.0000PT 0.0000PT; ">
<00000 00000 =" 000000-000000: 00000; 00000-0000000-000000: 00; 000: 000000 (51,51,51);</pre>
'\[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \] \[ \
MSO-FONT-Kerning: 0.0000pt; ">
000000pt; MSO-FONT-Kerning: 0.0000pt;
">0000000000<00000 = "00000-000000: 00000; 00000-000000-00000-00000-00000: 00; 000:
[][]: 12.0000PT; MSO-FONT-Kerning: 0.0000pt; ">
MSO-FONT-Kerning: 0.0000pt; ">
<_____ =" _______: MSO-ASCII-FONT-FAMILY: CALIBRI; MSO-HANSI-FONT-</pre>
000000: 0000000; MSO-BIDI-FONT-FAMILY: '000000 0000 0000'; 000000-00000: 12.0000PT; MSO-
MSO-FONT-Kerning: 0.0000pt; ">
<00000 = "00000-00000: 00000; 00000-00000-00000: 00; 00; 000: 00000 (51;51,51);</pre>
MSO-FONT-Kerning: 0.0000pt; ">
```

```
| 12.0000PT; MSO-FONT-Kerning: 0.0000pt; ">
```

Chassis model		SX11858J501	Chassis brand	SHACMAN	
Overall dimensions		8290x2370x2760mm	Wheel base	4700mm	
Front/rear wheel track		1880/1800mm	Front/rear suspension	1430/2160mm	
Approach/departure angle		20/13°	Maximum speed	90km/h	
Chassis Manufacturer		Shaanxi Automobile Group Co. LTD			
Cab	Configuration	L3000 cab, hydraulic mechanical flip, channel type instrument panel, air conditioner, allowable 3 passengers			
	Color	white, other color is optional			
Engine	Model	WP6.210E32			
	Emission	Euro 3			
	Туре	6 cylinders,in-line,4-stroke,water-cooled,turbo inter-cooling,diesel engine			
	Rated power	210hp,rated power speed 2500rpm			
	Displacement	5900ml			
	Max.torque	640N·m			
	Manufacturer	Weichai Power Co., Ltd.			
Tire	Size	10.00R20			
	Number	6+1 nos			
Clutch	push type diaphragm spring clutch,Φ395mm				
Frame	(250x80x[7+4])mm				
Fueltank	160L,steel				
Front axle	4.8T				
Rear axle	10T				
Drive form	4X2				
Rated voltage	24V,DC				
Transmissions	Gearbox 8JS85T, 8 speed forward 1 reverse.				
Steering device	Power assisted steering				
Steering wheel	Left hand drive				
Selective configur	ation				

Equipment		
Structure	Body, sub frame, lifting rear part, the loading device, the pushing-out plate, hydraulic and electric systems	
Loading capacity	14m3	
System of loading	Mechanized, rear loading	
Modes of the pressing	Manual,semi-automatic,automatic,lifting rear part operation manual,loading,pushing,pressing, pushing out automatic	
Standard configuration	Chassis,arc-shaped body,sub frame,rear lifting part,loading bunker,pushing-out plate,hydraulic system,pressing system,sewage tank,climbing ladder,pneumatic control.	
Selective configuration	PLC electric automatic control,multifunctional rear lifting part,rear handrail and footplate,other shapes of body,rear swing arm,and etc.	



















