

Saya.Spesifikasi utama

Model Produk□nama

CLW9400GYT Trailer Tangki Bahan Api (Trak Kimia)

Jumlah berat (kg)

39800

Dimensi Keseluruhan (mm)

12980 × 2500 × 3820

Muatan (kg)

28000

Hang depan/belakang (mm)

-/1860

Berat Curb (kg)

11800

Jarak roda (mm)

7200+1310+1310

Volum Tangki (M3)

44

Pendekatan/Sudut Berlepas (°)

-/16

Bilangan gandar

3

Beban gandar (kg)

-/23850 (tiga paksi)

Tangki bahan

Q235B keluli karbon

Ketebalan tangki

Gandar

Fuhua13t□Fuhua15t □16T atau BPW12T□14t pilihan□

Menyokong kaki

28t

Titik tunda

90#

li.thers

Trak dilengkapi dengan mulut tangki standard euro, tangga anti-slipping, laluan keselamatan, keranjang, kotak air, elektrostatik tali pinggang, alat pemadam api, kotak alat, rak tayar ganti dan sebagainya.

III.Instructions

Dilengkapi dengan pelbagai plat bukti gelombang, tangki mempunyai ciri -ciri kekuatan tinggi, kestabilan yang sangat baik, selamat pengangkutan .. mengikut keperluan pelanggan, tangki boleh dibahagikan kepada banyak petak untuk minyak yang berbeza□Dalam tambahan□pam minyak□ meter aliran,□cecair penunjuk tahap□injap bawah □paip pemanasan□Penebat lapisan dan peranti lain adalah pilihan□Apa 's more, 1-3 aliran diri mulut atau lebih boleh dipasang di bahagian belakang dan sisi tangki.it Bergantung pada pelanggan' keperluan.

liii.applications

Untuk minyak pengangkutan

. 45000 liter treler tangki bahan api

Imej produk



PRODUCT DETAILS

01

Oil Tanker Semi Trailer is a tanker with a trailing head connected to the trailing section. Compared with the conventional single tanker tanker tanker, oil transport can effectively improve the transportation efficiency. In the same tonnage situation, reduce transportation costs, saving fuel consumption.



02

The tank body is made of 4mm or 6mm high-quality carbon steel according ,The shape of the tank body is divided into oval or square round tanks, which can contain 1-4 kinds of oil products. Can also produce heating and heat preservation series tanks.



03

A plurality of anti-wave baffles are arranged in the tank body. High pressure gas leak test is adopted to ensure that the tank body has high strength, stable center of gravity and safe and stable vehicle transportation.



PRODUCT ADVANTAGES

1. Heavy duty and extra durability designed; Opting for high tensile steel Q345B, welded by automatic Submerged-Arc processes.
2. Heavy machinery suspension with leaf spring.
3. Two-line brake system with automatic brake system/chamber.
4. Welding tightness is strictly tested for solid tires, which are highly elastic and wear-resistant.
5. The material of the storage tank can be aluminum alloy, carbon steel, stainless steel, etc.



