

Main specification			
Product model and name	CSC5060TQZB Aumark Wrecker truck		
Gross weight(Kg)	6495	Drive type	4X2
Curb weight(Kg)	5000	Overall dimension(mm)	7500x2300x2400
Approach/departure angle(°)	22/11	Cab seats	3
Axle No.	2	Front/rear hang(mm)	1120/2460
Axle load(Kg)	2400/4095	Wheelbase(mm)	3800
Max speed(Km/h)	95		
Chassis specification			
Chassis model	BJ1069VCJEA-D	Manufacturer	Beiqi Foton Auto Co.,Ltd
Brand name	FOTON	Dimension(mm)	6725x2100x2280
Tyre specification	7.50R16	Tyre No.	6
Steel spring number	9/11+7	Front track base(mm)	1685
Fuel type	Diesel	Rear track base(mm)	1600
Emission standard	Euro 3	Transmission	6 forwarder gear,1 reverse gear(manual)
Cab	Single row, luxurious interior trim with seats.Cab can be tippable forwardly.And power steering with air condition.		
Engine model	Engine manufacturer	Displacement(ml)	Power(Kw)
CY4102-C3C	Dongfeng Chaoyang chaochai Power Co.,Ltd	3856	88(120HP)
Performance			
Flat length(mm)	5600	Flat width(mm)	2300
Max pulling weight(Kg)	4000	Max lift weight(Kg)	3000
Vehicle accessories			
Training wheels, Steel wire rope, Bandage, Alarm lamp, Tyre covers, Jack, Spare tyre, Drivers' tools			
Wrecker Truck Instruction			
The full name of wrecker truck is named road wrecker truck, also called trailer and road rescue truck. It has the powerful function and can carry two cars at the same time. It is the ideal choice for road management department and automobile repair plat to proceed to the road repair and rescue.			

FOTON Aumark 4TON Road Tow Truck Image



Wrecker Tow Truck Operation Image



Wrecker Tow Truck Detailed Parts



Wrecker Tow Truck in Bulk Exported

