

General Technical Parameters		
Overall Dimension		8500X2470X3330 (mm)
Gross Vehicle Weight		15900 (Kg)
Curb Weight		8295 (Kg)
Chassis Specification		
Chassis Brand		ISUZU FTR
Drive model		4*2
Cabin		Single Row, LHD, with air condition.
Number of Passengers		3
Engine	Model	4HK1-TC51/205HP
	Power	151KW/205HP
	Emission standard	EURO 5
	Displacement	5193(ml)
	Fuel type	Diesel
Gearbox		Isuzu MLD 6 speed transmission, manual operation, with power steering.
Brake System		Oil break
Wheel Base		4500mm
Front/Rear Axle Loading		4990/7500 (Kg)

Approach/Departure Angle	30/21(°)
Overhang	Mechanical Suspension, 9/11+8
Tire	11.00R20, 6pc with 1 spare tire
Max Driving Speed	90 (km/h)

Upperstructure Specification		
Garbage Hopper	Dimension	4200×1850×1400mm
	Standard	With one garbage bin, with
	Configuration	hydraulic rear outrigger
	Volume	Ground type, 8CBM
	Loading Capacity	10Ton
	Thickness	5mm, Carbon Steel Q235B
Dump type	Hydraulic cylinder lifting and self-loading	
Dump angle	$\geq 45^{\circ}$	
Hydraulic system pressure	$\leq 16\text{Mpa}$	
Protective Material	Q235A Carbon Steel	
Controlling Way	Three-way hydraulic control valve	
Other Configuration	inforced hydraulic swept-body system, with Double draulic cylinder Swing Arm, Chain. Hydraulic multi-way valve control.	
Options	Electronically controlled valve, trash bin type, trash bin quantity, etc.	

Gambar rujukan:







