

Vehicle size (mm)		8770×2550×3420
Total mass (kg)		18000
Rated quality (kg)		13750
Chassis Model		QL1180EQFRY
Cab	Crew	6
	Type	VC61;2 rows,4 door
	Air conditioning	Heating and cooling
	Direction assistance	Exist
	Central lock	Exist
	steering wheel	Multifunction steering wheel
	dash board	Multifunctional LCD instrument panel
	Doors and windows	Electric doors and windows
Frame		Frame section:172×65×4+3mm
Front axle (t)		6.3t
Rear axle (t)		15Tdash board
Wheel base (mm)		4500
Axle number		2
Wheel		295/80R22.5 16PR (6set)
Engine	model	ISUZU Brand 6HK1-TCG61, Diesel ,6-cylinder
	power	177KW/240HP
	Displacement	7790ml
Torque (N.m)		860
Gearbox		Fast,8 forward,1 reverse
Brake assembly		Air brake
Top speed		105km/h
Fuel tank		200L
Vehicle Special Parts Configuration		
Tank capacity		6000-7000L,Q235 Carbon Steel
Fire monitor	Model	Chengdu West Model: SP40
	Range	≥65m 1.0Mpa
	Flow	40L/S
	Other	-30°~+70°; 0~360°
Fire pump	Model	CB10/40-RS
	pressure	1.0MPa
	Flow	40L/S
	Diversion	≤35S
	suction depth	7m
	Shaft power	68.2KW

Others	fire electric siren:1-nos emergency rotation lamp:1-nos fireman's axe:1-nos fire hook:1-nos fireman <u>ladderextension</u> ladder 30 metal ladder:1-nos jet&spray nozzle:1-nos jet nozzle:1-nos Fire hoses(B/S System;o65mm,20m):4-nos suction pipe(length 4m,o100mm):2-nos water filter(metal)and guide rope:2-nos suction pipe wrench(o100mm):2-nos fire hydrant wrench:2-nos pipe quality is high. to contain fire extinguisher.(3kg) seat of hydraulic jack and wheel spanner high quality.
--------	--

Mga Larawan ng Sanggunian:





Whatsapp & Telephone: +86-18607222773 Email: brenda@ciclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@ciclwtruck.com

Product details

01 EQUIPMENT CONFIGURATION

Free 6 technical documents, at least 34 fire extinguishing equipment and 7 demolition rescue tools



02 FIRE FIGHTING PUMP

With independent fire pump room, operation is convenient for fire fighters. according to capacity, we have CB10/20, CB10/30,CB10/40,CB10/60

03 FIRE FIGHTING GUN

Reliable performance, high pump flow rate high, far throw range. According to capacity, we have PS20,PS30,PS40,PS50



04 CONTROL INTEGRATION

With intelligent control integration system, ensure the stability of the entire operating vehicle. The whole truck body anti preservative treatment, welding is firm, smooth and even.

04

Small size fire truck



2000L



3000L



4000L

Medium size fire truck



6000L



8000L



10000L

Big size fire truck



12000L



16000L



20000L

