Teknikal na pagtutukoy

Name	ISUZU Fire Truck	2	Chassis Model	QL10703HWRY				
Vehicle parameters	GVW(kg)	6545	Overall Dimension (mm)	6350×1980×2750				
	Rated load (kg)	2000	Steering Wheel	LHD				
	Curb weight (kg)	4170	Wheelbase (mm)	3360				
	Driving Type	4*2						
Engine parameters	Mode1	4JB1CN	Emission Standard	Diesel, Euro 4				
	Horse Power (hp)	98	Displacement (ml)	2771				
	4 stroke, 4-cylinders in line, water cooling							
Gear box	5 forward and 1	and 1 reverse						
Performance Parameter	Max Speed (km/h)	95	Wheel Tread(mm)	Front Axle	1504			
	Cab Seat	2+3		Rear Ax1e	1425			
	Leaf Spring	8/6+5	Suspension (mm)	Front Suspension	1015			
	Tire No.	6+1		Rear Suspension	1880			
	Tire Specification	7.00R15	Driving Angle(°)	Approach Angle	24			
	Ax1e No.	2		Departure Angle	14			
Special Function	Capacity	Water tank 2500L						
	0.00	mp 1. CB10/20, 20L/S,pressure:1.0MPa 2.Suction time≤ 35s (7m suction depth) centrifugal pump						
		1.PS20, 20L/S, pressure: 1.0Mpa 2. Fire nozz1e range: water≥45m						
Performance Description	Double row cab with 4 doors; Hidden tank, material is carbon steel Q235A, with thickness 4 mm; Truck body with aluminum alloy rolling door; PTO control indicator installed in cab, also with 100W siren, LED alarm lams sign light, lighting switch, rear lighting and etc.							

Larawan ng Fire Truck















Product details

01

EQUIPMENT CONFIGURATION

Free 6 technical documents, at least 34 fire extinguishing equipment and 7 demolition rescue tools





FIRE FIGHTING PUMP

With independent fire pump room, operation is convenient for fire fighters. according to capacity, we have CB10/20, CB10/30,CB10/40,CB10/60

03

FIRE FIGHTING GUN

Reliable performance, high pump flow rate high, far throw range. According to capacity, we have PS20,PS30,PS40,PS50





CONTROL INTEGRATION

With intelligent control integration system, ensure the stability of the entire operating vehicle. The whole truck body anti preservative treatment, welding is firm, smooth and even.

04