

Specifications

Sweeping vehicle refers to the vehicle that undertakes the cleaning, washing and cleaning of urban or national highway, highway and other roads. The vehicle has two brush discs, a wide suction disc, or four trays, and a rear suction port. Type of road operation vehicles.

- 1. We can supply all brands of special trucks, such as Dongfeng, ISUZU, Sinotruck, Foton, Faw, north Benz(beiben), JAC, JMC, etc.**
- 2. The drive type could be 4X2, 4X4, 6X4, 6X6, 8X4**
- 3. Certification: ASM, ISO, BV, SGS, CCC etc.**

Advantage:

- 1. The garbage bin is made of stainless steel with a filter plate inside, which can effectively prevent light objects such as leaves from blocking the air outlet and dust from being discharged.**
- 2. Anti-corrosion, anti-rust and anti-virus treatment inside the water tank.**
- 3. The cleaning structure of "Center 4 brush + rear suction cup", the front sweeping disk has automatic obstacle avoidance function, and the left and right sweeping brushes can be controlled separately.**
- 4. According to the user's needs, it can be equipped with pre-shooting, post-sprinkling, spraying, self-cleaning reel, operation monitoring system, auxiliary suction device and snow shovel.**

DongFeng BRAND 5-7CBM ROAD SWEEPER TRUCK

Main specifications

Product model□name

CLW5090TSL3 Road Sweeper Truck

Gross weight(Kg)	9400	Drive type	4 X 2
Payload (Kg)	3500	Overall dimension (mm)	6700×2290×2500
Curb weight(Kg)	5705	cab seats (man)	3
Approach / departure angle(°)	22/12	Front/rear hang(mm)	1180/1720
Number of axles	2	Wheelbase(mm)	3800
Axle load	3460/5940	Max speed(Km/h)	90
Chassis specifications			
Chassis model	EQ1090T9ADJ3AC	Manufacturer	DongFeng Motors Co., Ltd.
Brand name	DongFeng	Overall dimension(mm)	6695×2285×2480
Tire specification	7.50R16	Tires No.	6
Steel spring number	11/9+7,8/10+7	Front track(mm)	1831
Fuel type	Diesel	Rear track(mm)	1640
Emission standard	Euro III	Transmission	5 forward gear,1 reverse gear
Cabin	Car interiors, with the direction of power and USB interface, cassette player, with air conditioning,		
Engine model	Engine manufacture	Displacement(ml)	Power(Kw)
CY4102-E3C	DongFeng Chaoyang Diesel Co.,Ltd	3856	91
Road Sweeper Performance			
Trash tank volume (m³)	5	Water tank volume (m³)	2.5
Material of trash tank	Stainless steel	Material of water tank	Stainless steel
Model of auxiliary engine	JX493G	Power of auxiliary engine(Kw)	57KW
Manufacturers of auxiliary engine	JiangXi ISUZU Engine Co., Ltd.	Max sweeping width(mm)	3200
Sweeping speed (km / h)	3-20	Sweeping capacity □□/h□	9000- 60000
Maximum Grain size and quality (mm)	100mm±1.5kg	Cleaning Rate	96%
Road Sweeper Features			

- 1.The control box is in the cab, all kinds of system electrical centralized to control, and easy to operate!
- 2, Four scan disk combined with suction nozzle in working. according to a different cleaning conditions Scan disk speed can be controlled by choosing three gear-High, medium and low, which can make sure there be have a good cleaning results in a variety of pollution status. and when met the obstacle, the scan disk can be have a automatic avoidance protections and features automatic reset function, and retracted automatically, then reseted automaticly after over some obstacles!
- 3.Both of side of the scan disk can be working altogether, or unilateral work independently.
- 4.The core components of hydraulic systems adopts the original import!

Image as below:



Whatsapp & Telephone: +86-18607222773 Email: brenda@clwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@ciciwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com





Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com