## **Technical Specification:**

<b>Main specifications</b>						
Product model name CLW5161JSQT3 Truck With Crane						
Gross vehicle weight(kg)	15800	Drive	Drive type		4 x 2	
Payload(kg)	7500	cab s	cab seats (man)		3	
Curb weight(Kg)	8105	Overa	all dimension	(mm)	9000×2490×3600	
Approach/departure angle (°)	32/15	-	nternal nsion(mm)		6140×2294×550	
Number of axles	2	Front	/rear hang(mi	m)	1250/2650	
Axle load(Kg)	5900/9900	Whee	elbase(mm)		5100	
Max speed(Km/h)	80					
Chassis specification	ns[]					
Chassis model	EQ5160GKJ1	Bran	Brand name		Dongfeng	
Manufacturer	Dongfeng Motor Corporation	Tires	Tires No.		6	
Approach/departure angle (°)	32/22	Tire	Tire specification		10.00R20	
Steel spring number	9/10+8	Fron	Front track(mm)		1940	
Fuel type	Diesel	Rear	Rear track(mm)		1860	
Emission standard	Euro III	Tran	smission		6 gears	
Cabin	Blue other colors are available , Flat, luxurious interior trim and seat, with air conditioning.					
Engine model	Engine manufactu	rer Displaceme		nt(ml)	Power(Kw)	
B190 33	Dongfeng Cummins E Co., Ltd	Engine 5900			140	
<pre>Crane specification[</pre>	]					
Crane model	SQS157	Type of Crane		Telescopic boom Crane		
Max lifting weight[]kg[]	6300	Max li	Max lift height[]m[]		11 / 12.8	
Working radius(m)	9/11		Operation method		High seat control / Side control	
Number of arms	3/4	Outrigger (pcs)		2/4		
[Functions]	· · · · · · · · · · · · · · · · · · ·		· · · ·			
hydraulic lifting and tele	escopic system. In g I stability of the true	jeneral ck, reai	, H-type outrig outrigger als	gger is e	cargo lifting and moving through equipped to realize its stability. To e equipped if the customer	

require. The truck can 360 ° continuously rotate.

 $4 \ x \ 2 \ Dongfeng \ 6300 \ kg \ Telescopic \ Boom \ Crane \ Truck Product Image:$ 















