

Chassis	
Overall Dimension	8950x2500x2950mm
Gross Vehicle Weight	11000 kg
Curb Weight	9080 kg
Loading Weight	6725 Kg
Wheel Base	4500 mm
Front/rear Tread	1210/2320mm
Approach/Departure Angle	24/10 degree
Front Axle	5000kg
Rear Axle	10000kg
Engine	Diesel Engine, watering cooling, four stroke, 6 cylinder in line
Engine horsepower	162 HP EURO III
Max Driving Speed	90 km/h
<u>Carbin</u>	3 Passenger allowed, Left Hand Driving, with Air Conditioner
Tire	10.00R20 (6 pieces+1piece spare tire)
Upper part	
Asphalt Tank	12 <u>cbm</u> 12000liters
Outside Material	Stainless plate
Insulation layer	≤20°C/8h
Bitumen pump	QGB950; 950L/min
Hydraulic System	
Hydraulic pump	CQB550-L
Driving Motor	05-110-BD31
Proportional Valve	EFBG-03-160-HF/Taiwan brand
Shuttle Valve	Shanxi <u>Yuci</u> brand
Overflow Valve	Shanxi <u>Yuci</u> brand
Control System	
Control System	CLW-30-01/Germany Siemens
Control Method	Manual and computer control
Smart asphalt nozzle	36 <u>pcs</u>
Heating System	
Heating method	Automatic heating by oil

Burner	Italy brand
Radiator	<u>Risheng</u> brand
Heat transfer oil pump	40-25-160
Gasoline Engine	6 kw
Spreading Width	6m
Spreading Speed	0.2~3L/min
Spreading Precision	±2%

Product Image:









Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com







Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com





Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com