the equipment of LPG Bobtail Truck:

- 1. pressure meter
- 2. temperature meter
- 3. Emergency cut off valve
- 4. safe valve
- 5. safe liquid and gas outlet
- 6. LPG Pump

General	Overall Dimension	7000×2300×2600mm		
	Total Mass	7045Kg		
	Rated Payload	2500Kg		
	Kerb Weight	4395Kg		
Cabin	Cab Capacity	2 persons allowed		
	Air Conditioner	With air conditioner		
Engine	Model/Rated Power	YC4E140-33 / 140HP		
	Туре	4-cylinder inline		
	Displacement	4256ml		
	Emission Standard	Euro 3		
	manufacturer	China Engine		
Chassis	Drive Type	4X2, Left Hand drive		
	Transmission	5forwards 1reverser		
	Wheelbase/No. of axle	3800 mm / 2		
	Tyre Specification	7.50R16		
	Tyre Number	6 tyres and 1 spare tyre		
	Max Speed	95 km/h		
	Paint	Metallic paint		
performance parameter	Capacity of tank	5000Liters		
	Inner diameter	1500mm		
	Lenght of tank body	3070mm		
	Tank body net weight	2832kgs		
	Design pressure	1.77Mpa		
	Design temperature	50℃		
	Thickness of tank body	10mm		
structural	Elliptical head, round tank			
style				
Inspection test	proof pressure	2.30Mpa		
	Air tightness test pressure	1.77Mpa		
	Pressure after gas replacement	0.05-0.1Mpa		
	Non-destructive testing ratio	100%		
	Oxygen content in tank	<3%		
	name	model	specs	QΤ
	Floating Ball Level Meter	UQZ-25P	1500	1
	Pressure meter	Y-100T	0-4Mpa	1
Safety	Temperature meter	WTQ-280	-40°C-60°C	1
accessories	Safe valve	A412F-25-14	DN50/DN25	1/1
	Emergencey cutoff valve	QGJ43F-25-7-8	DN50/DN25	2/2
	Shut off valve	J24Q-64	DN6	2
	Ball valve	Q41F-25P-8B/9B	DN50/DN25	1/1
Other	LPG Pump			
attached	25m length hose reel.			
components:				
Painting	One anti corrosion and zinc-rich prim- customer need.	er and final painting	will be accor	dance v

Reference pictures



















