☐Main specifications ☐				
Product model name	CLW5250JSQ3 Truck With Crand	е		
Gross vehicle weight(kg)	25000	Drive type		6 x 4
Payload(kg)	9815	cab seats (man)		3
Curb weight(Kg)	14990	Overall dimension (mm)		11980×2500×3750
Approach/departure angle (°)	20/13	Box internal dimension(mr	n)	8500×2294×550
Number of axles	3	Front/rear hang(mm)		1460/2870
Axle load(Kg)	7000/18000	Wheelbase(mm)		5700+1300
Max speed(Km/h)	90			
☐Chassis specifications ☐				
Chassis model	DFL1250A9	Brand name		Dongfeng
Manufacturer	Dongfeng Motor Corporation	Tires No.		10
Approach/departure angle (°)	20/16,15,13	Tire specification		11.00-20
Steel spring number	8/9	Front track(mm)		2040
Fuel type	Diesel	Rear track(mm)		1860/1860
Emission standard	Euro III	Transmission		9 gears
Cabin	D310 flat standard cab, airbag	shock absorber driver seat, o	channel da	shboard, with air conditioning
Engine model	Engine manufacturer	Displacement(ml)		Power(Kw)
C260 33	Dongfeng cummins engine co., LTD	8300		191
☐Crane specification ☐				
Crane model	SQS250	Crane brand	XCMG	
Type of Crane	Straight boom crane	Crane weight(kgs)	2800	
Max lifting weight∏kg∏	12000	Max lift height[]m[]	14.5	
Working radius(m)	12.5	Operation method	High seat	control
Number of arms	4	Outrigger (pcs)	4	
[Functions]				

The truck consists of chassis, box, power take-off and crane, achieving cargo lifting and moving through hydraulic lifting and telescopic system. In general, H-type outrigger is equipped to realize its stability. To be further strengthened stability of the truck, rear outrigger also can be equipped if the customer require. The truck can 360 ° continuously rotate.

## 6x4 Dongfeng Kinland 12 ton Lorry Mounted Crane

## **Product Image:**











