

| Main specifications | | | |
|---|---|---|---------------------------------|
| Product model,name | | CLQ5160ZYS4HN Compression Garbage Truck | |
| Gross weight(Kg) | 16000 | Driving type | 4*2 |
| Payload (Kg) | 7000 | Overall dimension (mm) | 7120*2480*3100 |
| Curb weight(Kg) | 8805 | Cab seats (man) | 3 |
| Approach/departure angle (°) | 20/18 | Front/rear hang(mm) | 1520/1800 |
| Axle No. | 2 | Wheelbase (mm) | 4800 |
| Axle load(Kg) | 6000/10000 | Max speed(Km/h) | 90 |
| Chassis specifications | | | |
| Chassis model | HN1160C16C8M4J | Manufacture | Anhui valin automotive co., LTD |
| Brand name | CAMC | Overall dimension (mm) | 6700*2400*2860 |
| Tire specification | 9.00-20 | Tires No. | 6+1 |
| Steel spring number | 9/9+6 | Front track(mm) | 1910 |
| Fuel type | Diesel | Rear track(mm) | 1800 |
| Emission standard | Euro 4 | Gear box | 6 forward and 1 reverse |
| Cab | Cab can flip forward, flat head, with a sleeper, with power assistance and AC | | |
| Engine model | Engine manufacture | | Displacement(ml) |
| YC4E160-42 | Guangxi yuchai machinery co., LTD | | 4260 |
| | | | 118 |
| Performance | | | |
| Body capacity(m3) | 12 | Hopper capacity(m3) | 1.8 |
| Compression cycle time(S) | 30 | Unload garbage time(S) | 40 |
| Control system | Manual + Automatic | | |
| Main Characteristic | | | |
| 1,Can choose 240L(single bin,double bins)or 360L,660L,1100L standard bin lifting and turnover mechanism,can also choose ground hopper and other kinds of loading mechanism. | | | |
| 2,With manual and automatic two sets of control method, the operator can control in the cabin, in the middle side or the back of the truck , very convenient and efficient. | | | |
| 3,With working device of emergency braking stop button. | | | |
| 4,Garbage body use frame design, elegant, strong structure, large effective capacity. | | | |
| 5,Equipped with special collection box, sewage directly into the sewage tank in the process of compression, that is effectively prevent second pollution caused by sewage leaks. | | | |
| 6,Through hydraulic system design, the truck achieve the function of two-way garbage compression, that is improve the compressibility ,make the compression ratio up to 1:2.5,the garbage can reach more then 600~800kg/m3 after compression. | | | |

CAMC 12 CBM Garbage Compacting Truck

Product Image:





Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com





Whatsapp & Telephone: +86-18607222773 Email: brenda@clewtruck.com

