| 3cbm Carbon Steel Arm Lift Garbage Truck |   |                       |              |
|--|---|-----------------------|--------------|
| Vehicle Parameters                       |   |                       |              |
| General                                  | Vehicle Model   | YZR5030ZXXS           |              |
|  | Vehicle Brand   | XDR                   |              |
|  | Chassis Brand   | Changan (SC1031GDD52) |              |
|  | Overall Dimension(mm)   | 4160×1520×1930        |              |
|  | GVW/Curb Weight/Rated   | 2840/1280/1430        |              |
|  | loading weight (kg)   |                       |              |
| Chassis Parameters                       |   |                       |              |
| Cab                                      | Cab Seat  | 2                     |              |
|  | Air Conditioner   | Optional              |              |
| Engine                                   | Fuel Type   | Gasoline              |              |
|  | Engie Model   | Dk12-10               |              |
|  | Engine Brand  | Chongqing xiaokang    |              |
|  | Power(kw/hp)  | 65/88                 |              |
|  | Displacement(cc)  | 1240                  |              |
|  | Emmission Standard  | Euro5                 |              |
| Chassis                                  | Drive Type  | 4*2                   |              |
|  | Transmission  | 5 speed, Manual       |              |
|  | Wheelbase(mm)   | 2700                  |              |
|  | Tyre Specification  | 165R14LT              |              |
|  | Tyre No.(pcs)   | 4                     |              |
|  | Max Speed(km/h)   | 90                    |              |
|  | Paint   | Customized            |              |
| Garbage Tank Structu                     | ure Parameters  |                       |              |
| Tank Volume                              | 3cbm  | Tank Material         | Carbon Steel |
| Tank Thickness                           | 2/3mm   | Max. Lifting Force    | 1-1.5ton     |
| Lifting Up Time                          | ≤15s  | Lifting down Time     | ≤10          |
| Dumping time                             | ≤10s  | Operation mode        | Manual       |
| Characteristic                           | 1.compact design and structure 2.three modes of operation:<br>electrical,manual,combined 3. oil filter equipped on fuel tank 4.high<br>strength cast material 5. cast supporter with wear plate,low noise 6.<br>swallow tail design 7. galvanized shaft 8.integrative lock<br>with safety limit device,more safe 9.strengthen arm |                       |              |

## The above information is for reference only. We can produce according to your needs. Please add my WhatsApp at 0086-18607222773(phone number as same).

Reference pictures[]















## • FACTORY SHOW •



## BUSINESS PARTNER •

