Technical Specification:

Main specifications				
Product model[]name	CLW5253JSQ3 Truck With Crane			
Gross vehicle weight(kg)	24900	Drive type		6 x 2
Payload(kg)	14120	cab seats (man)		3
Curb weight(Kg)	10585	Overall dimension (mm)		11200×2500×3750
Approach/departure angle (°)	34/12	Box internal dimension(mm)		7800×2294×550
Number of axles	3	Front/rear hang(mm)		1205/3295
Axle load(Kg)	6750/6780/11370	Wheelbase(mm)		1950+4750
Max speed(Km/h)	85			
Chassis specifications				
Chassis model	EQ5253GFJ3	Brand name		Dongfeng
Manufacturer	Dongfeng Motor Corporation			8
Approach/departure angle (°)	34/20	Tire specification		10.00R20
Steel spring number	10/10/12+9	Front track(mm)		1940/1940
Fuel type	Diesel	Rear track(mm)		1860
Emission standard	Euro III	Transmission		8 gears
	Flat cab, luxurious interior trim and seat, and sleeper. The cab can flip			
Cabin	forward, with power steering, air conditioning can be equiped if customer			
	requires.			
Engine model	Engine manufacturer	Displacement	:(ml)	Power(Kw)
B210 33	Dongfeng cummins engine c LTD	, 5900		140
Crane specification				
Crane model	SQS200	Crane brand	CLW	
Type of Crane	Telescopic boom crane	Crane weight (kg)	2700	
Max lifting weight[]kg[]	8000	Max lift height[]m[]	13.5	
Working radius(m)	11.5	Operation method High seat control /		at control / Side control
Number of arms	4	Outrigger (pcs)	2/4	
[]Functions[]				

The truck consists of chassis, box, power take-off and crane, achieving cargo lifting and moving through hydraulic lifting and telescopic system. In general, H-type outrigger is equipped to realize its stability. To be further strengthened stability of the truck, rear outrigger also can be equipped if the customer require. The truck can 360 ° continuously rotate.

China Dongfeng 6x2 8-10 tons Truck-mounted crane, Straight Boom Crane Truck Manufacturer

Product Image:







