Main specifications							
Product model, name		CLQ5310GYY5D fuel tanker truck					
Gross weight(Kg)		31000		Driving type		8x4	
Payload (Kg)		18735		Overall dimension (mm)		11990×2500×3300,369 0	
Curb weight(Kg)		12135		Cab seats (man)		3	
Approach/departure angle (°)		26/10		Front/rear hang(mm)		1460/3030	
Axle No.		4		Wheelbase (mm)		1950+4250+1300	
Axle load(Kg)		6500/6500/1800 0		Max speed(Km/h)		80	
Chassis specification	าร		v.				
Chassis model		311A4	Manu	ifacture	Do	Dongfeng Motor Co.,Ltd	
Brand name	DongFeng		Overall dimension (mm)		11475×2500×3030,3600,36 90		
Tire specification	295/80R22.5		Tires No.		12+1		
Steel spring number	8/8/10		Front track(mm)		1940/1940		
Fuel type	diesel		Rear track(mm)		1860/1860		
Emission standard	Euro 3		Gear box		12 forward gears and 2 reverse gears		
Cab	D310 Flat top and double cab, gasbag shock the driver seat, single dashboard, with air conditioning						
Engine model	Engine manufacture			Displacement(ml )		ower(Kw)	
L340 33	Dongfeng Cummins Engine Co., LTD		9460 25		50		
Performance							
Tank capacity (Liter)	32000						
Tank material	Q235 carbon steel。						
Transport medium	Petrol or diesel。						
Main Characteristic							
A, with multiple baffle	plates	in the tank, t	he tank	k has the advantag	es o	f high intensity, stability,	

- **A,** with multiple baffle plates in the tank, the tank has the advantages of high intensity, stability, transporting safety etc.
- B, Oil pump is installed to suck or discharge oil, with high suction pressure and speed.
- **C**, according to users' needs, the tank can be designed as a single compartment or several compartments to contain different oils.
- ${\bf D}$ , according to users' needs, the side or the rear of the tank can be installed 1 to 3 self-flowing valves.

Reference pictures []











