| Product model, name | | | CSC5060ZYS3 Compression Garbage Truck | | | | | | | |
|--|--|-----------|---------------------------------------|------------------------|-----------------------------|-----|-----------------|-----------|--|---|
| Gross weight(Kg) | | | | Driving type | | | 4*2 | | | |
| Payload (Kg) | | | | Overall dimension (mm) | | | \$450°2850°2500 | | | |
| Curb weight(Kg) | | 5365 | | Cab seats (man) | | 2 | | | | |
| Approach/departure angle (*) | | 19/10 | | Front/rear hang(mm) | | | 1032/2118 | | | |
| Axie No. | | 2 | | Wheelbase (mm) | | | 3300 | | | |
| Axie losd(Kg) | | 2570/3925 | | Max speed(Km/b) | | | 95 | | | |
| Chassis specifications | | | | | | | | | | |
| Chassis model | | | Manufacture | | Dongfeng automobile company | | | | | |
| Brand name | Dongfeng | | Overall dimension (mm) | | 5820*1940*2080 | | | | | |
| Tire specification | | | Tires No. | | 6+1 | | | | | |
| Steel spring number | | | Front truck(mm) | | 1506 | | | | | • |
| Fuel type | | | Rear track(mm) | | 1466 | | | | | |
| Emission standard | | | Gear box | | 5 forward | | | | | |
| Cab | Flat single cub, luxurious interiors and seats, air conditioning is optional | | | | | | | | | |
| Engine model | Engine manufacture | | | | Displacement(ml) | | | Power(Kw) | | |
| CY4102-C3F | Dongfeng chaoyang chaochai | | | | 3856 | | 70 | | | |
| Performance | | | | | | | | | | |
| Body capacity(m ¹) | | | Hopper capacity(m ²) | | | 0.8 | | | | |
| Compression cycle time(S) 30 | | | Unload garbage time(S) | | 40 | | | | | • |
| Control system Marzual +Auto | | | ulorantic | | | | | | | |
| Main Characteristic | | | | | | | | | | |
| Care close 2004 Comply his deaths leader 2004,0001,11004, closed bin litting and traverse reclasions, can since those growed degree and the Care Michaelman of the close and the close of t | | | n more then 600–800kg/m3 after | сопревыба. | | | | | | |

DFAC Garbage Truck

Image as below:















