

| | | | |
|-------------------------------|---|-------------------------------|---------------------------|
| Main specifications | | | |
| Product model name | JDF5072TSLDFA4 Road Sweeper Truck | | |
| Gross weight(Kg) | 7300 | Drive type | 4 X 2 |
| Payload (Kg) | 2000 | Overall dimension (mm) | 6150×2230×2550 |
| Curb weight(Kg) | 5170 | cab seats (man) | 2 |
| Approach / departure angle(°) | 19/11 | Front/rear hang(mm) | 1032/1818 |
| Number of axles | 2 | Wheelbase(mm) | 3300 |
| Axle load | 2920/4380 | Max speed(Km/h) | 95 |
| Chassis specifications | | | |
| Chassis model | DFA1070SJ35D6 | Manufacturer | DongFeng Motors Co., Ltd. |
| Brand name | DongFeng | Overall dimension(mm) | 5845×1900×2220 |
| Tire specification | 7.00R16 | Tires No. | 6 |
| Steel spring number | 8/9+5,6/8+4,6/6+5 | Front track(mm) | 1506 |
| Fuel type | Diesel | Rear track(mm) | 1466 |
| Emission standard | Euro IV | Transmission | 5 forward gear, oil brake |
| Cabin | Available move forward with the direction of power , optional air conditioning, | | |
| Engine model | Engine manufacture | Displacement(ml) | Power(Kw) |
| D28D10-4DA | Dongfeng Light Engine Co., Ltd. | 2771 | 75 |
| Road Sweeper Performance | | | |
| Trash tank volume (m³) | 4 | Water tank volume (m³) | 1.5 |
| Material of trash tank | Stainless steel | Material of water tank | Stainless steel |
| Model of auxiliary engine | JX493G | Power of auxiliary engine(Kw) | 57KW |

| | | | |
|--|--------------------------------|----------------------------|-------------|
| Manufacturers of auxiliary engine | JiangXi ISUZU Engine Co., Ltd. | Max sweeping width(mm) | 3200 |
| Sweeping speed (km / h) | 3-20 | Sweeping capacity □□/h□ | 9000- 60000 |
| Maximum Grain size and quality (mm) | 100mm\±1.5kg | Cleaning Rate | 96% |
| Road Sweeper Features | | | |
| <p>1.The control box is in the cab, all kinds of system electrical centralized to control, and easy to operate!</p> <p>2, Four scan disk combined with suction nozzle in working. according to a different cleaning conditions Scan disk speed can be controlled by choosing three gear-High, medium and low, which can make sure there be have a good cleaning results in a variety of pollution status. and when met the obstacle, the scan disk can be have a automatic avoidance protections and features automatic reset function, and retracted automaticly, then reseted automaticly after over some obstacles!</p> <p>3.Both of side of the scan disk can be working altogether, or unilateral work independently.</p> <p>4.The core components of hydraulic systems adopts the original import!</p> | | | |

DFAC 4x2 Road sweeper truck

Image as below:



Whatsapp & Telephone: +86-18607222773 Email: brenda@clcwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@cclwtruck.com







Whatsapp & Telephone: +86-18607222773 Email: brenda@clwtruck.com







Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com