## **Technical Specification**

Tooming Spooms and I							
Main specifications							
Product model name		ALA5090GXWE3 Sewage suction truck					
Gross weight(Kg) Payload (Kg)  Curb weight(Kg) Approach/departure angle (°)		9400		Driving type Overall dimension (mm) Cab seats (man) Front/rear hang(mm)		4x2	
		4700 4505 22/13				6700×2350x2650	
						3	
						1180/1720	
Axle No.		2		Wheelbase (mm)		3800	
Axle load(Kg)		3460/5940	)	Max speed(Kn	n/h)	95	
Chassis specifications							
Chassis model	EQ1090T9ADJ3A C		Manufacture			ongfeng Automobile Ompany	
Brand name	Dongfeng		Overall dimension(mm)		66	95×2180×2350	
Tire specification Steel spring number	8.25R16		Tires No.		6		
	11/9+7,8/10+7		Front track(mm)		17	50	
Fuel type	Diesel		Rear track(mm)		18	56	
Emission standard	Euro III		Gear box		5 <u>g</u>	gears	
Cab	luxuriou	luxurious interior trim and seat, single cab, with air conditioning.					
Engine model	Engine manufacture			Displacem ml)	ent(	Power(Kw)	
CY4102-E3C	Dongfeng Chaoyang Diesel Co.,Ltd			3856		91	
Tank body							
Tank capacity[]m³[	_		Tanl	k material	Q235	carbon steel	
Main Characteristic							

The truck is equipped with high-powered vacuum suction pump and high quality hydraulic system. With rear lid of the tank opened hydraulically, and double cylinders on both sides of the tank lifting up, the truck can dump the sewage directly through the rear lid out of the tank. Characterized by high vacuum, large capacity, high efficiency and good seal, the truck is widely used. Full tank pumping time:  $\leq 5$ min; suction width:  $\geq 8$ m. Very suitable for sucking sewer sediments, such as mud, silt, stones, bricks and other big objects.

## DFAC 6000 Liters Sewage Suction Truck

**Product Image** 













