Technical Parameters:

| Main Specification | S | | | | | | | |
|--|---|-----------------------------|----------------------|---|----------------------------|-----------|---------------|--|
| Product number,name Total weight (Kg) | | compression garbage to 9400 | | ruck Drive mode | | 1 * 2 | 4 * 2 | |
| Weight (kg) | | 2500 | | Dimensions (mm) | | | 7150 * 2285 * | |
| Curb Weight (KG) | | 6705 | | Cab seats (MAN) | | 2950 3 | 2950 3 | |
| Approach / departure angle) | | 20/10 | | Suspended before / after hanging (mm) Wheelbase (mm) Maximum speed (km / h) | | • | 1180/2170 | |
| Axle No. | | 2 | | | | | 3800 | |
| | | 3290/6110 | | | | | | |
| Axle load (KG) | | | | | | 95 | 95 | |
| Chassis Specifications | | | | | | | | |
| Chassis Type | EQ1090T9AD | 3AC | manufacture | | Dongfeng Motor Corporation | | | |
| Brands Dongfeng | | Dimension | | | | 285 * 235 | 85 * 2350 | |
| Tire specifications | 7.50R16 | Tire No. | | 6 + 1 | | | | |
| Spring steel | 11/9 7 + | Front track | | | | | | |
| Fuel type Emission Standards | diesel engine | Rear track Gearbox | | (mm) 1640 5 forward | | ı | | |
| taxi | Europe iii Ping single ca | h luxury Inte | | | | | | |
| engine model | Ping single cab, luxury Interiors and seats, air-conditioning is optional Displacement | | | | | | | |
| engine model | Engine Manufacturer | | | | (ml) | | Power (Kw) | |
| CY4102-E3C | Dongfeng Chaoyang Chaoyang Diesel E Company Limited | | | Engine | 3856 | | 91 | |
| performance | | | | | | | | |
| Body size(Meter ³) | | | Hopper c | | ³) 1 | | | |
| Compression Cycle Time(small) | thi | rty | Unloadin time(sma | g garbage all) | 4 | 0 | | |
| Control System | На | ndbook + au | | | | | | |
| main feature | | | | | | | | |

- 1,Optional 240L(single box,Double barrel)Or 360L,660L,1100L TEU lifting tilting mechanism,were able You can also choose other types of ground hopper loading mechanism.
- 2,There are two sets of manual and automatic control Method, the operator can control the cabin or in the middle of the back side Truck, very convenient and effective.
- 3,Emergency braking device stops working button.
- 4, Garbage body with a frame design, elegant appearance, solid structure, Large effective capacity.
- 5, With a special collection box, sewage Direct access during compression cesspool that Effectively prevent secondary pollution caused by sewage leaks.
- 6,Hydraulic system design, realization truck Bi garbage compression function, which is to improve the compression The compression ratio up to 1: 2.5, the garbage can reach more than $600 \sim 800$ kg/Compressed cubic meters.

Dongfeng Motor 4X2 8CBM compression garbage truck

Product Image:















