| Main Technical Para             | meters 🔲  |   |  |
|---------------------------------|---|---|--|
| Production name                 | DONGFENG Right<br>Hand Drive<br>Mobile food truck | GVW(kg)                                 | 4220   |
| Rated weight(Kg)                |   | Overall dimensions(mm)                  | 5995 *2120 *3350                               |
| Curb weight(kg)                 | 2225  | Cabinet size(mm)                        | 4200 *2000 *1950                               |
| Approach/departure<br>angle(°)  | 19/15   | F/R overhang(mm)                        | 1032/1663                                      |
| Number of axles                 | 2   | Wheel base(mm)                          | 3300   |
| Axle-load(Kg)                   | 1800/2695   | Max speed(Km/h)                         | 95   |
| Transmission                    | 5 forward gears and<br>1reverse                   | Cab                                     | Single row, Luxury interior and Instrument bar |
| Chassis Technical Pa            | rameters 🔲  |   | •  |
| Chassis model                   | EQ1060TJ20D3                                      | Number of tire                          | 6+1  |
| Brand                           | Dongfeng  | Manufacturer                            | Dongfeng Automobile Company (DFAC)             |
| F/R<br>track base(mm)           | 1506/1466   | Tire specification                      | 7.00R16(High quality steel wire tire)          |
| Fuel Type                       | Diesel  | Emission standard                       | Euro II  |
| Engine Technical Parameters [   |   |   |  |
| Engine model                    | D28D10-3D3  | Displacement (ml)                       | 2771   |
| Engine manufacturer             | Dongfeng light engine<br>co., LTD                 | Max power(Kw)                           | 75   |
| Max Torque/<br>Speed (Nm/r/min) | 345/1300~1500                                     | Max Horsepower(hp)                      | 102  |
| Compression ratio               | 15.5  | Minimum fuel<br>Consumption<br>(g/kw.h) | 205  |

## Standard configuration:

The internal and outside of the compartments is made of cold-rolled steel sheet material and the floor made of skidproof , waterproof and wear-resistant aluminum checkered plate; The top of the compartments is closed and can not open, but the left and right side and the back can be expanded and there is vending bar on both left and right side. The internal compartments is installed with LED vending floodlights or two columns spotlight (5pcs / column), top exhaust fan, megaphone, master switch, USB interface, large space locker; The outside of the compartments is installed two loudspeakers, 105A battery, 220V external power supply interface , 15m external power supply cord, telescopic truck pedal; different truck color and skin stickers are optional .

## DONGFENG mobile fast food truck for sale















