## **Truck With Crane**

<b>Main specifications</b>				
Product model name				
Gross vehicle weight(kg)	25000	Drive ty	ре	6×4
Curb weight(Kg)	8575	Overall	dimension (mm)	12000×2550×3850
Number of axles	2 Box int dimens		rnal on(mm)	8500×2450×550
Axle load(Kg)	7000/18000 Wheelbas		ise(mm)	5900+1350
Max speed(Km/h)	88			
Chassis specifications		·		
Chassis model	EQ1253GSZ6DJ		Brand name	Dongfeng
Manufacturer	Dongfeng Automobile Co., Ltd.		Fuel type	Diesel
Tires No.	10		Tire	11.00r20 18PR
			specification	
Front track(mm)	1960		Rear track(mm)	1860/1860
Emission standard	VI		Transmission	9J
Engine Power(kw)	199			
<pre>[Crane specification]</pre>				
Crane model	SQS300-5	Crane brand		CLW
Type of Crane	Straight-arm crane	Crane weight (kg)		4200
Max lifting weight[]kg[]	12000	Max lift height[]m[]		20.5
Working radius(m)	18.5	Operation method		Operating the equipment
Number of arms	5	Outrigger (pcs)		4
[Functions]				

The truck consists of chassis, box, power take-off and crane, achieving cargo lifting and moving through hydraulic lifting and telescopic system. In general, H-type outrigger is equipped to realize its stability. To be further strengthened stability of the truck, rear outrigger also can be equipped if the customer require. The truck can 360 ° continuously rotate.





















Automatic constant-temperature radiator—no manual intervention required; cools down automatically upon reaching the set temperature



Features the same dual-pump system with dual-pump confluence as top Chinese crane brands—large displacement, high hydraulic pressure, excellent stability, and strong pressure