Dongfeng Kingrun 12CBM fresh milk transporting truck

| Dongfeng Kingrun fresh             | milk transporting true   | ck  |  |
|------------------------------------|--|---|--|
| 16000                              | Drive type   | 4*2   |  |
| 9000                               | oversize(mm)   | 8200×2480×3180  |  |
| 6805                               | Drive seat(people)   | 3   |  |
| 26/23                              | front/rear hang(mm)  | 1205/2495   |  |
| 2                                  | wheelbase(mm)  | 4500  |  |
| 6000/10000                         | Max speed(Km/h)  | 90  |  |
| 13                                 | Standard compartme   | ents 3  |  |
| er                                 |  |   |  |
| EQ1141KJ                           | manufacturer   | Dongfeng commercial<br>vehicle Co.,ltd  |  |
| Dongfeng                           | oversize(mm)   | 8455×2460×2610  |  |
| 10.00-20                           | Tyre no.   | 6   |  |
| 9/11+8                             | Front track(mm)  | 1940  |  |
| diesel                             | Rear track(mm)   | 1860  |  |
| Euro III                           | Gear box   | 8 forward,1 reverse   |  |
|                                    |  | eat,sliding cabin,with  |  |
| Engine manufacturer                | displacement(ml)   | power(Kw)   |  |
| Dongfeng cummins engine<br>Co.,ltd | 5900   | 140   |  |
|                                    |  |   |  |
|                                    | 16000   9000   6805   26/23   2   6000/10000   13   er   EQ1141KJ   Dongfeng   10.00-20   9/11+8   diesel   Euro III   153 flat one and half row,lux   power steering, air condition   Engine manufacturer   Dongfeng cummins engine | 9000oversize(mm)6805Drive seat(people)26/23front/rear hang(mm)2wheelbase(mm)6000/10000Max speed(Km/h)13Standard compartmeerEQ1141KJEQ1141KJmanufacturerDongfengoversize(mm)10.00-20Tyre no.9/11+8Front track(mm)dieselRear track(mm)Euro IIIGear box153 flat one and half row,luxurious interior and sepower steering, air condition for optionEngine manufacturerdisplacement(ml)Dongfeng cummins engine5900 |  |

1. The tank is made of food-grade stainless steel and used to transport milk and other liquid food. It is safe and reliable.

2. Multiple tanks are set to unload the materials separately, which can transport a variety of liquid food at the same time.

3, heat preservation function: lifting [] 1 °C of the temperature of the tank medium 24 hours a day. 4. Equipped with PIC cleaning device, easy cleaning inside the tank.

5. Standardized parts are convenient for maintenance.

| 1 |  |  |
|---|--|--|
|   |  |  |
|   |  |  |
|   |  |  |











## FACTORY SHOW •



















## BUSINESS PARTNER •

