

Main specifications			
Product model name	CLW5090JSQ3 Truck With Crane		
Gross vehicle weight(kg)	9495	Drive type	4 x 2
Payload(kg)	4200	cab seats (man)	3
Curb weight(Kg)	5100	Overall dimension (mm)	7995×2440×3100
Approach/departure angle (°)	22/11	Box internal dimension(mm)	5100×2150×550
Number of axles	2	Front/rear hang(mm)	1180/2415
Axle load(Kg)	3440/6055	Wheelbase(mm)	4400
Max speed(Km/h)	90Km/h		
Chassis specifications			
Chassis model	EQ1090TJ12D5	Brand name	Dongfeng
Manufacturer	Dongfeng Motor Corporation	Tires No.	6
Approach/departure angle (°)	22/11	Tire specification	8.25-16
Steel spring number	11/13+8	Front track(mm)	1770
Fuel type	Diesel	Rear track(mm)	1602
Emission standard	Euro III	Transmission	5 gears
Cabin	Blue other colors are available, Flat, luxurious interior trim and seat, with air conditioning.		
Engine model	Engine manufacturer	Displacement(ml)	Power(Kw)
YC4E140-33	Guangxi Yuchai Machinery Co.,Ltd	4260	105
Crane specification			
Crane model	SQS84 / SQS100	Crane brand	XCMG
Type of Crane	Telescopic boom	Crane weight (kg)	1220
Max lifting weight kg	4000	Max lift height m	10 / 11.5
Working radius(m)	7.93 / 9.4	Operation method	High seat control / Side control
Number of arms	3 / 4	Outrigger (pcs)	2 / 4
Functions			
The truck consists of chassis, box, power take-off and crane, achieving cargo lifting and moving through hydraulic lifting and telescopic system. In general, H-type outrigger is equipped to realize its stability. To be further strengthened stability of the truck, rear outrigger also can be equipped if the customer require. The truck can 360 ° continuously rotate.			

Dongfeng 4000 kgs Truck Mounted XCMG Crane, China Truck Mounted Crane Manufacturer









Kindly note we can provide straight boom crane and folding crane according to customers' requirement. And the crane also can be equipped on flatbed truck for transport construction machinery like excavator, wheel loader, harvest ect undisassemble machines.



