Main specifications							
Product model,name		CLW5100BZLT3 Swing Arm Garbage Truck					
Gross weight(Kg)		10990	Driving type		4*2		
Payload (Kg)		4000	Overall di	mension (mm)	7370)*2470*3300	
Curb weight(Kg)		6795	cab seats	(man)	3		
Approach/departure angle (°)		33/16	Front/rea	Front/rear hang(mm)		1250/2170	
Axle No.		2	Wheelbas	e (mm)	3950)	
Axle load(Kg)		3970/7020	Max spee	d(Km/h)	90		
Chassis specifications							
Chassis model	EQ1110GLJ		Manufact	Manufacture		Dongfeng motor company	
Brand name	Dongfeng		Overall dimension (mm)		7120*2462*2710		
Tire specification	9.00-20		Tires No.	Tires No.		6+1	
Steel spring number	8/11+8		Front trac	Front track(mm)		1900	
Fuel type	Diesel		Rear tracl	Rear track(mm)		1800	
Emission standard	Euro I I		Gear box	Gear box		5 forward	
Cab							
Engine model	Engine manufacture			displacement(ml)		Power(Kw)	
YC4E160-33	Guang	xi yuchai machine	ery co.,ltd	4257		118	
Performance							
The bin capacity(m³)	8		Bin materi	Bin material Q2		235 carbon steel	
Control system	Full hydraulic						
Characteristic							

The characteristics of the truck is the bin can be separated from the body, by hydraulic lifting operation , the bin can hanging up and down, working cycle time for one swing arm is 60s or less, that can achieve a truck with multi-bins combination operate, cyclic transportation. The truck also with dump function, the garbage can dump out directly from the bin. In general, the bin can be installed in the pit, also can be placed on the ground, according to customers demand, you can choose to add a sealed lid, which can prevent the garbage leak float in the sky that pollute the environment.

Dongfeng 8 CBM Swing Arm Garbage Truck

Product Image:









