

<b>Main specifications</b>			
Product model/name	CLW5161JSQT3 Truck With Crane		
Gross vehicle weight(kg)	15800	Drive type	4 X 2
Payload(kg)	6850	cab seats (man)	3
Curb weight(Kg)	8755	Overall dimension (mm)	9000×2490×3600
Approach/departure angle (°)	32/18	Box internal dimension(mm)	5800×2294×550
Number of axles	2	Front/rear hang(mm)	1250/2550
Axle load(Kg)	5900/9900	Wheelbase(mm)	5100
Max speed(Km/h)	80		
<b>Chassis specifications</b>			
Chassis model	EQ5160GKJ1	Brand name	Dongfeng
Manufacturer	Dongfeng Motor Corporation	Tires No.	6
Approach/departure angle (°)	32/22	Tire specification	10.00R20
Steel spring number	9/10+8	Front track(mm)	1940
Fuel type	Diesel	Rear track(mm)	1860
Emission standard	Euro III	Transmission	8 gears
Cabin	Blue other colors are available, Flat, luxurious interior trim and seat, with air conditioning.		
Engine model	Engine manufacturer	Displacement(ml)	Power(Kw)
B210 33	Dongfeng Cummins Engine Co., Ltd	5900	155
<b>Crane specification</b>			
Crane model	SQS200	Crane brand	XCMG
Type of Crane	Telescopic boom	Crane weight (kg)	2700
Max lifting weight[kg]	8000	Max lift height[m]	13.5
Working radius(m)	11.5	Operation method	High seat control / Side control
Number of arms	4	Outrigger (pcs)	2 / 4
<b>Functions</b>			
The truck consists of chassis, box, power take-off and crane, achieving cargo lifting and moving through hydraulic lifting and telescopic system. In general, H-type outrigger is equipped to realize its stability. To be further strengthened stability of the truck, rear outrigger also can be equipped if the customer require. The truck can 360 ° continuously rotate.			

## Dongfeng 8 Ton Telescopic Boom Crane Truck

Product Image







Kindly note we can provide straight boom crane and folding crane according to customers' requirement. And the crane also can be equiped on flatbed truck for transport construction machinery like excavator, wheel loader, harvest ect undisassemble machines.





