Dongfeng Kinland 6x4 fuel transport truck

Main technical parameter			
Product name	CLQ5250GYY3 fuel transport truck		
Gross weight(Kg)	24900	Drive type	6*4
Rate loading(Kg)	14200	oversize(mm)	10400×2490×3350
Curb weight(Kg)	10505	Cabin seat(person)	3
approach/departure(°)	29/16	front/rear hang(mm)	1250/3050
Axle no.	3	wheelbase(mm)	4350+1300
Axle weight(Kg)	7000/17900(2 axles)	Max speed(Km/h)	80
Chassis technical parameter			
Chassis model	DFL1250A8	Chassis name	truck[]second[]
brand	Dongfeng	manufacturer	Dongfeng Motor Co.,Ltd
oversize(mm)	11700×2470×2850	Tyre no.	10
approach/departure(°)	32/19	Tyre specification	10.00-20
Steel spring no.	9/10	Front track(mm)	1960
Fuel type	diesel	Rear track(mm)	1860/1860
Emission standard	Euro III	Gear box	8 forward,1 reverse
Engine model	Engine manufacturer	displacement(ml)	power(Kw)
C260 33	Dongfeng cummins engine Co.,ltd	6170	190
performance			
Tank volume[]L/m³[]	25		
Tank material	Q235 carbon steel		
Transport medium	Gasoline or diesel		
description			

with multiple baffle plates in the tank, the tank has the advantages of high intensity, stability, transporting safety etc

According to users' needs, the tank can be designed as a single compartment or several compartments to contain different oils.

C.According to users' needs, the side or the rear of the tank can be installed 1 to 3 self-flowing valves.

Product Image:











