

## Technical Specification:

[Main specifications]			
Product model,name	EQ5166JSQZM Truck With Crane		
Gross vehicle weight(kg)	15800	Drive type	4 X 2
Payload(kg)	6555	cab seats (man)	3
Curb weight(Kg)	9050	Overall dimension (mm)	9000×2500×3850
Approach/departure angle (°)	18.5/9.5	Box internal dimension(mm)	5500×2300×550
Number of axles	2	Front/rear hang(mm)	1430/2570
Axle load(Kg)	5800/10000	Wheelbase(mm)	5000
Max speed(Km/h)	90		
[Chassis specifications]			
Chassis model	DFL1160BX6A	Brand name	Dongfeng
Manufacturer	Dongfeng Motor Corporation	Tires No.	6
Approach/departure angle (°)	18.5/12	Tire specification	9.00-20 16PR
Steel spring number	8/9+7	Front track(mm)	1800
Fuel type	Diesel	Rear track(mm)	1680
Emission standard	Euro IV	Transmission	6 gears
Cabin	Flat cab, tiltable luxurious interior trim, seat, and sleeper. with power steering, air conditioning can be equipped if customer requires.		
Engine model	Engine manufacturer	Displacement(ml)	Power(Kw)
EQH160-40	Dongfeng commercial vehicle Co., LTD	4752	118
[Crane specification]			
Crane model	SQS157	Crane brand	XCMG
Type of Crane	Telescopic boom crane	Crane weight (kg)	2102
Max lifting weight(kg)	6300	Max lift height(m)	11 / 12.8
Working radius(m)	9 / 11	Operation method	High seat control / Side control
Number of arms	3 / 4	Outrigger (pcs)	2 / 4
[Functions]			
The truck consists of chassis, box, power take-off and crane, achieving cargo lifting and moving through hydraulic lifting and telescopic system. In general, H-type outrigger is equipped to realize its stability. To be further strengthened stability of the truck, rear outrigger also can be equipped if the customer require. The truck can 360 ° continuously rotate. Special used for cargo lifting and transportation of the larger wheel loaders or crawler loaders. The Cargo platform can extend to 3m.			

## Dongfeng Kingrun 6300 Kgs Truck Mounted Crane with Basket

### Product Image



