

Dongfeng Kinland Detachable Container Garbage truck

Main Technical Parameter			
Product name	CSC5250ZXXD11 detachable container garbage truck		
Gross weight(Kg)	25000	Drive type	6*4
Rate loading(Kg)	13050,12985	oversize(mm)	8500×2500×3100
Curb weight(Kg)	11820	cabinet(mm)	××
Cabin seat(people)	2,3	Utilization factor of payload	
approach/departureangle(°)	20/20	front/rear hang(mm)	1460/1340
Axle no.	3	wheelbase(mm)	4350+1300
Axle weight(Kg)	7000/18000(2 axles)	Max speed(Km/h)	90
Chassis technical parameter			
Chassis model	DFL1250A8	Chassis name	truck[]second[]
brand	DONGFENG	manufacturer	Dongfeng Commercial Vehicle Co.,Ltd
oversize(mm)	9240×2500×3030	Tyre No.	10
approach/departure(°)	20/14	Tyre specification	11.00R20
Steel spring No.	8/9	Front track(mm)	1986,2040
Fuel type	diesel	Rear track(mm)	1860/1860
Emission standard	Euro III	Gear box	5forward,1 reverse
Cabin	310flat single bed cabin[]All welded steel hydraulic machinery tilting cab[]semi-floating cab,rear mechanical damping[]adjustable seat,with air conditioner, electric window,central lock		
Engine model	Engine manufacturer	displacement(ml)	power(Kw)
C260 33	Dongfeng Cummins Engine Co.,Ltd	6700	190
Performance			
Tank volume[]m³[]	16	Tank material	Q235 carbon steel
Unloading type	Rear unload	Operation type	manual+electric

Detachable container garbage truck also called pull arm garbage truck;

Using full hydraulic control,the operator can do the waste bin lifting,discharging and dumping both in the driving room or out of the room,and all the operations can be performed by one driver in the cab;

Reference pictures[]







Whatsapp & Telephone: +86-18607222773 Email: brenda@ciclwtruck.com









Whatsapp & Telephone: +86-18607222773 Email: brenda@clewtruck.com