

Main specification				
Product model and name		Water and Foam Tank Fire Truck		
Gross weight(Kg)	14900	Drive type	4x2	
Payload(Kg)	6070	Overall dimension(mm)	7900X2470X3390	
Curb weight(Kg)	8380	Cab seats	3	
Approach/departure angle(°)	25/15	Front/rear hang(mm)	1205/2135	
Axle No.	2	Wheelbase(mm)	4500	
Axle load(Kg)	4900/10000	Max speed(Km/h)	85	
Chassis specification				
Chassis model	EQ1141KJ	Manufacturer	Dongfeng Auto Co.,Ltd	
Brand name	Dongfeng	Tyre No.	6	
Tyre specification	10.00-20	Front track base(mm)	1940	
Steel spring number	8/10+8	Rear track base(mm)	1860	
Fuel type	Diesel	Transmission	8 forward gear, 1reverse gear	
Emission standard	Euro 3			
Cab	Four opening doors and whole flat top with crew cab, and all steel frame welded structure.Air condition is optional.			
Engine model	Engine manufacturer	Displacement(ml)	Power(Kw)	Horsepower(HP)
B190 33	Dongfeng Cummins Engine Co.,Ltd	5900	140	190
Foam and powder fire truck performance				
Water tank volume(L)	4000-5000L	Foam tank volume(L)	1000L-2000L	
Fire monitor	Model:PL32. water and foam tank dual purpose fire monitor. Foam range:≥50m/1.0MPa Water range:≥55m/1.0MPa			
Fire pump	Model: CB10/40. Flow rate:40L/S. Pressure: 1.0MPa. Water pump drive type: sandwich type power take-off			
Feature				
Water and powder tank combination fire truck can spray water and powder at the same time.Adopted the independent passengers room and has 6 seats.Both dry powder and valves are made by stainless steel.This truck can be used to put out all kinds of fire,especially applied to save the liquid and gas fire etc.It is the indispensable fire extinguishing equipment for the fire department.				

Dongfeng 4X2 fire truck image



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@cleitruck.com









Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com