Main specification							
Product model and name		CLW5031X	CLW5031XLC4 Refrigerator truck				
Gross weight(Kg)			2920 Driv			4x2	
Payload(Kg)		1380		Overall dimension(mm)		4735*1650*2400	
Curb weight(Kg)		1410	1410 Cab			2	
Approach/departure angle(°)		25/15	25/15 Front		)	870/1165	
Axle No.		2				2700	
Axle load(Kg)		1170/1750	1750 Max speed(Km/h)			90	
Chassis specification							
Chassis model	DFA1030S	FA1030SJ40QD-KM		rer		Dongfeng Motor Group Auto Co.,Ltd	
Brand name	Dongfeng	ongfeng		(mm)		4665*1515*1940	
Tyre specification	175R13LT	175R13LT 8PR				4	
Steel spring number	5/5,5/6	5/5,5/6		base(mm)		1260	
Fuel type	Gasoline	Gasoline		base(mm)		1260,1340	
Emission standard	Euro 4		Transmissi	on		5forward gear,1 reverse gear	
Cab	Single row	ngle row, luxurious interiors and seats					
Engine model	Engine ma	anufacturer Displacement(r			Displacement(ml)	Power(Kw)	
LJ465Q-2AE	Liuzhou W	uling Liuji Power Co.,Ltd			1051	45(61hp)	
Performance							
an body size(mm) 3000*1480°		3000*1480*1500	*1500		ity(TON)	0.6 to1.5	
Lowest refrigeration temperature(°C) -5 to -18 Ce		-5 to -18 Centigrade	ntigrade				
Feature and Application							
The metric control to the placed one to the	that the same data than		and a Third to the self-		Litely of control Bullion	. (b	

The refrigerator truck is the closed van truck that is used to transport the frozen or fresh goods. This truck is made up of vehicle chassis, Polyurethane insulation van, refrigeration unit and temperature recorder. It is commonly used to transport the frozen food, dairy products, vegetable and fruit and vaccine medicine etc. For the special requirements of trucks, such as the meat transportation, the meat hook, aluminum alloy guide rail and ventilation slots etc. parts can be chosen and installed.

## Refrigerator truck

## Image as below:















