

FAW 8X4 16000-25000L fuel truck

| Main specifications                                                                                                              |                                                                                                                   |                        |                                    |
|----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|------------------------|------------------------------------|
| Product model□name                                                                                                               | CSC5253GYYC4A FAW fuel truck                                                                                      |                        |                                    |
| Gross weight(Kg)                                                                                                                 | 24520                                                                                                             | Driving type           | 8x4                                |
| Payload (Kg)                                                                                                                     | 13835                                                                                                             | Overall dimension (mm) | 10400×2480×3080                    |
| Curb weight(Kg)                                                                                                                  | 10490                                                                                                             | Cab seats (man)        | 3                                  |
| Approach/departure angle (°)                                                                                                     | 17/12                                                                                                             | Front/rear hang(mm)    | 1400/2400                          |
| Axle No.                                                                                                                         | 3                                                                                                                 | Wheelbase (mm)         | 1900+4700                          |
| Axle load(Kg)                                                                                                                    | 6510/6510/11500                                                                                                   | Max speed(Km/h)        | 80                                 |
| Chassis specifications                                                                                                           |                                                                                                                   |                        |                                    |
| Chassis model                                                                                                                    | CA5250GYYP62K1L6T3E4                                                                                              | Manufacture            | China First Automobile Works Group |
| Brand name                                                                                                                       | FAW                                                                                                               | Fuel type              | Diesel                             |
| Tire specification                                                                                                               | 10.00R20                                                                                                          | Tires No.              | 8+1                                |
| Front track(mm)                                                                                                                  | 1890/1890                                                                                                         | Rear track(mm)         | 1847                               |
| Transmission standard                                                                                                            | Euro IV                                                                                                           | Gear box               | 6 forward gear,1 reverse gear      |
| Cab                                                                                                                              | J6L half float flat row of half Cab , manual glass lifts, manual rearview mirror, with automatic air conditioning |                        |                                    |
| Engine model                                                                                                                     | Engine manufacture                                                                                                | Displacement(ml)       | Power(Kw)                          |
| F6M2012-22E4                                                                                                                     | China First Automobile Works Group                                                                                | 6060                   | 165                                |
| Performance                                                                                                                      |                                                                                                                   |                        |                                    |
| Tank capacity□L/m³□                                                                                                              | 16000-25000L (16-25/m³)                                                                                           |                        |                                    |
| Tank material                                                                                                                    | Q235 carbon steel□                                                                                                |                        |                                    |
| Transport medium                                                                                                                 | Petrol or diesel□                                                                                                 |                        |                                    |
| Main Characteristic                                                                                                              |                                                                                                                   |                        |                                    |
| □, with multiple baffle plates in the tank, the tank has the advantages of high intensity, stability, transporting safety etc.   |                                                                                                                   |                        |                                    |
| □, Oil pump is installed to suck or discharge oil, with high suction pressure and speed.                                         |                                                                                                                   |                        |                                    |
| □, according to users' needs, the tank can be designed as a single compartment or several compartments to contain different oils |                                                                                                                   |                        |                                    |
| □, according to users' needs, the side or the rear of the tank can be installed 1 to 3 self-flowing valves□                      |                                                                                                                   |                        |                                    |

As below photo show :











