1. The internal material is stainless steel external material is fiberglass, the middle is 8 cm polyurethane insulation plate,

double-sealed door, standard spray system, potion box, ultraviolet antivirus system.;2.Refrigerator configuration: the brand and

the temperature range can be delected according to the requirements of the goods, includes: Kaixue, Hanxue THERMO KING, carrier,

etc.

3. This vehicle is for Sealed and constant temperature transportation of disposable and contagious items for the medical industry.

Vehicle model	CA1122PK2L2Y (RHD)	
Cabin	single row	
Whole vehicle main dimensions	overall dimension(LxWxH)mm	8920*2530*3790
	Drive system	4X2
	wheel base(mm)	5050
	Rearoverhang	2050
Weight data	curb weight(kg)	6405
	loading weight(kg)	15000
	GVW	12500
Whole vehicle main performance	Max speed(km/h)	93
Engine	Engine	CA6110/125Z
	Туре	four-cylinder, in-line, water-cooling, DI, four-stroke, supercharger with intercooler, diesel engine
	displacement	7.127
	Max power(kw/rpm)	155/2600
	max torque(N.m/rpm)	560/1500-1700
Gearbox	gear box	CA6TBX085M,6 forward,1 reseve
	speedratio	i1:7.285,i2:4.193,i3:2.485,i4:1.563,i5:1,i6:0.783,jR:6.777
Rearaxle	435 Punching welding Bridge, speed ratio 5.571	
Steering gear	Powersteering	
Frame	237*75*7	
Clutch	Dry type, single plate, diaphragm spring clutch, hydraulic controlled, Air pressure booster, φ395	
Cabin	J5K,CAB on engine,metal closed,3 seats	
tyre size	Double coin 10.00R2016	
Cooling system	Cooling cargo dimension	6410*2310*2310
	cooling machine	HUATAI F600
	cargo material	glass fiber reinforced plastics
	cargothickness	8CM with polyurethane
	Other	Stainless steel lock, stainless steel Contour comer protection, stainless steel door frame, dome light and Bumper block, two rear door
Option	1,Side door, 2,refrigerator machine :thermoking, carrier ,and others you like	

Reference pictures[]















