Main specification							
Product model and name			HLQ5020XLCB Refrigerator truck				
Gross weight(Kg)			1875 Drive type		4x2		
Payload(Kg)		495		Overall dimension(mm)		4695×1600×2400	
Curb weight(Kg)		1250		Cab seats		2	
Approach/departure angle(°)		28/28,24	1/28	Front/rear hang(mm)		895/1100	
Axle No.		2		Wheelbase(mm)		2700	
Axle load(Kg)		780/109	5	Max speed(Km/h)		90	
Chassis specification							
Chassis model	BJ1020V3	V2-X		Manufacturer		Beiqi Foton Auto Co.,Ltd	
Brand name	Foton			Dimension(mm)		4435×1505×1760	
Tyre specification	165/70R1	3LT		Tyre No.		4	
Steel spring number	-/5,-/6	-/5,-/6		Front track base(mm)		1260	
Fuel type	Gasoline	Gasoline		Rear track base(mm)		1340	
Emission standard	Euro 4	Euro 4		Transmission		5 forward gear,1 reverse gear	
Cab	1500 sing	1500 single row, luxurious interiors and seats					
Engine model	Engine ma	Engine manufacturer			Displacement(ml)	Power(Kw)	
LJ465Q-2AE	Liuzhou W	Liuzhou Wuling Liuji Power Co.,Ltd			1051	45(61hp)	
Performance							
Van body size(mm)	body size(mm) 2550*141		*1490 Load capacity(TON)		0.6-1.5T		
Lowest refrigeration temperature(°C) -5°C to -:		-5°C to -18°C			•		
Feature and Application							

The refrigerator truck is the closed van truck that is used to transport the frozen or fresh goods. This truck is made up of vehicle chassis, Polyurethane insulation van, refrigeration unit and temperature recorder. It is commonly used to transport the frozen food, dairy products, vegetable and fruit and vaccine medicine etc. For the special requirements of trucks, such as the meat transportation, the meat hook, aluminum alloy guide rail and ventilation slots etc. parts can be chosen and installed.

## FOTON refrigerator truck















