

1	Product name		ISUZU 6000L refueling truck
2	Drive type		4x2
3	steering wheel		Left hand drive
4	Tank volume	M³ (L)	6
5	Overall size	mm	6180×2080×2700
6	Gross weight	kg	8280
7	Rated payload	kg	3935
8	Curb weight	kg	4150
9	Axle		2
10	Wheelbase	mm	3360
11	Max speed	Km/h	80
12	Chassis model		QL1070A5HAY
13	Chassis brand		ISUZU
14	Chassis manufacturer		<u>Qingling Auto motor Co.,Ltd</u>
15	Engine Model		4KH1CN5HS
16	Engine manufacturer		<u>QinglingISUZU(chongqing)engine</u> co.,ltd
17	Displacement/Power	ml/kw	2999/96KW/ 130HP
18	Emission		Euro 5
19	fuel type		Diesel
20	Tyre specification / Tyre number		7.00R16 / 6
21	Tank material and thickness		Q235 carbon steel, tank thickness 4.2mm,head thickness 4.5mm
22	oil pump		Yes
23	refueling machine		Large flow tanker ,with one refueling gun
24	automatic return oil pipe		15 M

25	European Standard opening		1 piece
26	sea valve		1 piece
27	<p>Usage: A. with multiple baffle plates in the tank,the tank has the advantages of high intensity,stability,transporting safety etc</p> <p>B. Oil pump is installed to suck or discharge oil,with high suction pressure and speed</p> <p>C. Computer refueling machine is selected,with a 15 meters automatic return oil pipe and refueling gun, achieving mobile refueling <u>fuction</u></p> <p>D. According to user's needs,the tank can be designed as a simple compartment or several compartments to contain different oils</p>		





