No.	Item name	unit	Specification/Technical Parameter	
1	Product name		ISUZU 30ton rotary wrecker truck	
2	Drive type		8x4	
3	steering wheel		Left hand drive	
4	Overall size	mm	13880×25500×4000	
5	Gross weight	kg	41000	
6	Rated payload	kg	27850	
7	Curb weight	kg	13150	
8	Axle		4	
9	Wheelbase	mm	2100+4325+1370	
10	Max speed	Km/h	85	
11	Chassis model		QL5440TZZW6VDHY	
12	Chassis brand		ISUZU	
13	Chassis manufacturer		Qingling Auto motor Co.,Ltd	
14	Engine Model		6WG1-TCG61	
15	Engine manufacturer		QinglingISUZU(China)engine co.,ltd	
16	Displacement/Power	ml/kw	15681/338KW/ 460HP	
17	Emission		Euro 6	
18	fuel type		Diesel	
19	Tyre specification / Tyre number		385/65R22.5	
20	Maximum lift weight(kg) In situ support		30-50ton	
21	winch		15*2	
22	three-section boom, thr linkage operating devic rope, equipped with fou of steel plate lifting lugs long row of engineering	Imported valves from Italy Hyde, Haizhanli oil cylinder, Wanye double pump, three-section boom, three-section support arm, split carriage, double-side linkage operating device, two 15-ton hydraulic winches, 45-meter steel wire rope, equipped with four sets of steel forks, one set of towing fork sets, one set of steel plate lifting lugs and towing forks, one set of tire holding device. One long row of engineering warning lights. One set of auxiliary lights, one set of auxiliary air pipe assembly, and two binding chains.		

Reference picture:

















