## **ISUZU 4-5.5CBM ROAD SWEEPER TRUCK**

Main specifications			
-	OL 1070A 1HAY, Dood Sweeper		
Product model[name	QL1070A1HAY Road Sweeper		1
Gross weight(Kg)	7300	Drive type	4 X 2
Payload (Kg)	2150	Overall dimension (mm)	6190x1990x2590
Curb weight(Kg)	5020	cab seats (man)	2
Approach / departure angle(°)	24/15	Front/rear hang(mm)	1015/1815
Number of axles	2	Wheelbase(mm)	3360
Axle load	2580/4720	Max speed(Km/h)	105
Chassis specification	15	•	
Chassis model	QL1070A1HAY	Manufacturer	ChongQing ISUZU Motors Co., Ltd.
Brand name	ISUZU	Overall dimension(mm)	5900×1880×2160
Tire specification	7.00-16	Tires No.	6
Steel spring number	8/6+5	Front track(mm)	1504
Fuel type	Diesel	Rear track(mm)	1425
Emission standard	Euro IV	Transmission	5 Forward Gear
Cabin	Luxury interior and Instrument l	oar, with air conditioning	J.
Main engine model	Engine manufacture	Displacement(ml)	Power(Kw)
4KH1-TCG40	ChongQing ISUZU Motors Co., Ltd.	2999	88
<b>Road Sweeper Perfo</b>	rmance		
Trash tank volume (m <sup>3</sup> )	04	Water tank volume (m <sup>3</sup> )	[]1.5
Material of trash tank	Stainless steel	Material of water tank	Stainless steel
Model of auxiliary engine	JX493G	Power of auxiliary engine(Kw)	57KW
Manufacturers of auxiliary engine	Jiangxi Isuzu Engine Co., Ltd.	Max sweeping width(mm)	3200
Sweeping speed (km / h)	3-20	Sweeping capacity	9000- 60000
Maximum Grain size and quality (mm)	100mm\±1.5kg	Cleaning Rate	96%
<b>Road Sweeper Featu</b>	res		

1. The control box is in the cab, all kinds of system electrical centralized to control, and easy to operate! 2, Four scan disk combinated with suction nozzle in working. according to a different cleaning conditions Scan disk speed can be controlled by choosing three gear-High, medium and low, which can make sure there be have a good cleaning results in a variety of pollution status. and when met the obstacle, the scan disk can be have a automatic avoidance

protections and features automatic reset function, and retracted automaticly, then reseted automaticly after over some obstacles!

3.Both of side of the scan disk can be working altogether, or unilateral work independently.

4. The core components of hydraulic systems adopts the original import!

Image as below:











