High Pressure ISUZU 6*4 clean truck

Vehicle name	Japanese 6x4 ISUZU 20000 liter Sewer cleaning suction truck	Volume (m3)	20
Dimensions (mm)	8150×2380×2920	Tank size (mm)	5350×1800×1300
Tank material	Carbon steel	Tank thickness (mm)	20
High pressure pump brand	Tianjin Tongjie / Italy Import	Pressure (Mpa)	16-19
Washing water flow rate (L/min)	120	Spray flow rate (L/min)	120
Cleaning width (m)	≥ 16	Washing water flow rate (L/min)	500-800
Flow rate (m3/h)	8	Water gun range (m)	38
Total mass (kg)	11450	Rated mass (kg)	6305
Curing quality (kg)	4950	Maximum speed (km/h)	103
Fuel type	Diesel	Emission Standards	Country five
Wheelbase (mm)	4600+1350	Tire specifications	295/80R22.5
Chassis brand / model	QL1250	Engine brand / model	I-SUZU
Power / horsepower (kW / ps)	257	Displacement (mL)	4500
Top loading configuration parameters			
The standard configuration	Install the sandwich power take-off, drive shaft, high-pressure cleaning pump, rated pressure 16Mpa, hydraulic reel, water level gauge, washing pipe, operation valve at the rear of the tank, equipped with a 60m 19mm high pressure pipe, 10 high pressure flushing heads.		
Optional configuration	Sprinklers, green sprinklers, front and rear sprinklers, side sprays, snow shovels, hydraulic lifting platforms, guardrail cleaning brushes can be added to meet the needs of different users.		

Reference pictures \square











