Advantages of Insulated Refrigerator Truck body:

The advantages of Insulated/Freezer Van Body

1. It is made of GRP and PU foam with all-closed structure that the GRP (Glass Reinforced Plastic Fiber) outside

and PU foam in the core.

- 2. Light in weight: 40% lighter than metal body.
- 3. Non-corrosion, non-pollution, anti-brine, acid and soda-resisting.
- 4. The panel used for the truck body was constructed in type of sandwich. The thermal insulation layer is 50-80mm

thick, which offers a very good thermal insulation performance.

5. Length of freezer truck body: 10-40 inch; Capacity of Cargo body: 5-70CBM. The material of the cargo body is optional

according to which kinds of goods the truck transport, with perfect heat preservation, box open model: Rear double-open or Side-open.

6. Refrigeration unit Brand Optioanl: American CARRIER, THERMO KING. South Korea hanya. China Songhan,

hanxue, etc. The Temperature range can be 0° C \sim -20° C. The refrigeration units that we select have simple

structure, convenient operation, reliable working, low energy consumption, large refrigerating capacity, small noise, easy installation and maintenance and other advantages for our refrigerated truck.

Overall Dimension	7025*2590*3300(mm)		Gross Vehicle Weight	8280(Kg)
Curb Weight	4085(Kg)		Loading Weight	4000(Kg)
		Chassis Sp	ecification	
Chassis parameters	Chassis Brand		ISUZU	
	Cabin		Single, Left Hand Driving, with A/C	
	Engine	Model	4KH1CN6HB, 4 Cylinders	
		Power	130HP	
		Emission standard	EURO VI	
		Displacement	2.999L	
		Fuel type	Diesel	
	Gearbox		MSB, 5 Forward & 1 Reverse Gear	
	Front and Rear Axle load		3.3T/5.5T	
	Wheel base		3815(mm)	
	Overhang(Front/Rear)		1130/1505(mm)	
	Angle(Approach/departure)		20/16(°)	
	Brake System		Oil brake	
	Steering Gear		Power Assistant	
	Tire		7.00R16 8PR, 6 Pieces with 1 Spare Tire	
	Maximum speed		105(km/h)	
		Superst	ructure	
Van	Box size		5020*2100*2100(mm)	
	Material		Fiberglass	
	Insulating Layer		8cm Polyurethane Foam	
Truck refrigeration unit	Brand		THERMOKING/CARRIER/other chinese brand	
	Applicable temperature (°C)		-18~0	
Remarks	Part Optional: Ventilation slot Hook External power supply			

Reference pictures:

















