## JAC 5T Compress Garbage truck

Main Specification			
Product name	HTW5080ZYSJH compress garbage truck		
Gross weight(Kg)	8280	Tank volume(m3)	8
Rate weight(Kg)	2285,2085,1935	oversize(mm)	6950,7200,7350,7050×2280×2680
Curb weight(Kg)	5800,6000,6150	Cabinet size(mm)	xx
Cabin seat (people)	3	Utilization factor of	
		payload	
approaching/departure	24/13	front/rear hang(mm)	1085/2050,1110/2025
angle(°)			
axle	2	wheelbase(mm)	3815
Axle weight(Kg)	3000/5280	Max speed (Km/h)	100
Chassis specification			
Chassis model	HFC1081P91K1C5ZV	Chassis name	Truck chassis (second)
Trademark name	JAC	manufacturer	Anhui JAC Motor Co.,Ltd
Tyre specification	7.50R16LT 14PR,8.25R16LT 14PR	Tyre no.	6
approaching/departure angle(°)	24/13		
Steel spring no.	8/6+6	Frong track(mm)	1685
Fuel type	diesel	Rear track (mm)	1600
Emission standard	Euro V		
Engine model	manufacturer	displacement(ml)	power(Kw)
WP3Q130E50	Weichai power	2970	96
	yangzhou engine Co.,ltd		
function	Inction  1 Can choose 240L single bin double bins or 360L 660L 1100L standard bin lifting and turnover mechanism can also choose ground hopper and other kinds of loading mechanism.  2 With manual and automatic two sets of control method, the operator can control in the cabin, in the middle side or the back of the truck, very convenient and efficient.  3 With working device of emergency braking stop button 4 Garbage body use frame design, elegant, strong structure, large effective capacity.  5 Equipped with special collection box, sewage directly into the sewage tank in the process of compression, that is effectively prevent second pollution caused by sewage leaks.  Through hydraulic system design, the truck achieve the function of two-way garbage compression, that is improve the compressibility, make the compression ratio up to 1:2.5, the garbage can reach more then 600 800 kg m3 after compression.		

Reference pictures  $\square$ 















## • FACTORY SHOW •



## BUSINESS PARTNER .































