Main specification							
Product model and name		CLQ5060XLCJX	CLQ5060XLCJX Refrigerator truck				
Gross weight(Kg)		4495	Drive t	Drive type		4x2	
Payload(Kg)		1100		Overall dimension(mm)		5995×2160×3030mm	
Curb weight(Kg)		3200	Cab se	Cab seats		2	
Approach/departure angle(°)		27/16	Front/r	Front/rear hang(mm)		1015/1615	
Axle No.		2	Wheel	Vheelbase(mm)		3360	
Axle load(Kg)		2200/3590	Max speed(Km/h)			80	
Chassis specification							
Chassis model	JX1060TG24			Manufacturer		Jiangling Auto Co.,Ltd	
Brand name	JMC	MC		Dimension(mm)		5825*1880*2020	
Tyre specification	7.00R16LT	7.00R16LT		Tyre No.		6	
Steel spring number	7/5+5		Front track base(mm)			1385	
Fuel type	Diesel		Rear track base(mm)			1425	
Emission standard	Euro 5	Transmission			5 forward gear,1 reverse gear		
Cab	Single row, luxurious interiors and seats with power steering. Air condition is optional.						
Engine model	Engine manufacturer				Displacement(ml)	Power(Kw)	
JX4D30A6H	Jiangling Auto Co.,Ltd				28920	95(130hp)	
Performance							
n body size(mm) 4080*2000*1950		000*1950	Load capacity(TON		ity(TON)	3	
Lowest refrigeration temperature(°C)	-5°C to -18°C			•			
Feature and Application							
The refrigerator truck is the closed van truck that is used to transport the frozen or fresh goods. This truck is made up of vehicle chassis, Polyurethane insulation van, refrigeration unit and							

The refrigerator truck is the closed van truck that is used to transport the frozen or tresh goods. This truck is made up or vehicle chassis, Polyurethane insulation van, refrigeration unit and temperature recorder. It is commonly used to transport the frozen food, dairy products, vegetable and fruit and vaccine medicine etc. For the special requirements of trucks, such as the meat transportation, the meat hook, aluminum alloy guide rail and ventilation slots etc. parts can be chosen and installed.

## JMC refrigerator truck

Image as below:











